



### Main

|                             |   |
|-----------------------------|---|
| Range of product            | NS630b...1600<br>Masterpact NT<br>Masterpact NW   |
| Range                       | Masterpact  |
| Device short name           | Carriage switch   |
| Product or component type   | Auxiliary contact   |
| Device application          | Control   |
| Range compatibility         | Masterpact - Masterpact NW<br>Masterpact - Masterpact NT<br>Compact - Compact NS630b...1600 |
| Offer type                  | C4  |
| Signal contacts composition | 1 NO/NC   |

### Complementary

|   |   |
|---|---|
| Auxiliary contacts type                     | Low level   |
| Auxiliary contacts operation                | Test position<br>Disconnected position<br>Connected position  |
| Mounting mode                               | Drawout   |
| [I <sub>e</sub> ] rated operational current | DC-12 : 0.3 A DC 250 V<br>AC-12 : 5 A AC 50/60 Hz 240 V<br>DC-12 : 0.8 A DC 125 V<br>DC-12 : 2.5 A DC 24/48 V<br>AC-12 : 5 A AC 50/60 Hz 24/48 V<br>AC-12 : 5 A AC 50/60 Hz 380 V |
| Minimum load                                | 2 mA at 15 V  |
| Accessory / separate part category          | Spare part Compact NS630b...1600<br>Spare part Masterpact NT<br>Spare part Masterpact NW  |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

33171