



Main

| | |
|-----------------------------|-------------------------------|
| Range | Compact |
| Range of product | NS630b...1600 |
| Product or component type | Circuit breaker |
| Product name | Compact NS |
| Device short name | Compact NS1000H |
| Circuit breaker name | Compact NS1000H |
| Device application | Distribution |
| Poles description | 4P |
| Protected poles description | 4t |
| Neutral position | Left |
| Network type | AC |
| Breaking capacity code | H |
| Suitability for isolation | Yes conforming to IEC 60947-2 |
| Utilisation category | Category B |
| Trip unit name | Micrologic 2.0 |
| Trip unit technology | Electronic |
| Trip unit rating | 1000 A (50 °C) |

Complementary

| | |
|--|--|
| Network frequency | 50/60 Hz |
| Control type | Rotary handle Toggle |
| Mounting mode | Fixed |
| Mounting support | Backplate |
| Upside connection | Front |
| Downside connection | Front |
| [In] rated current | 1000 A (50 °C) |
| [Ui] rated insulation voltage | 800 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 8 kV conforming to IEC 60947-2 |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Circuit breaker CT rating | 1000 A |
| Breaking capacity | 65 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 |

70 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2
 85 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2
 42 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2
 50 kA Icu at 500/525 V AC 50/60 Hz conforming to IEC 60947-2

| | |
|--|---|
| [Ics] rated service breaking capacity | Ics 52 kA 380/415 V AC 50/60 Hz conforming to IEC 60947-2 Ics 31 kA 660/690 V AC 50/60 Hz conforming to IEC 60947-2 Ics 37 kA 500/525 V AC 50/60 Hz conforming to IEC 60947-2 Ics 48 kA 440 V AC 50/60 Hz conforming to IEC 60947-2 Ics 52 kA 220/240 V AC 50/60 Hz conforming to IEC 60947-2 |
| Auxiliary contact composition | 1 NO/NC |
| Mechanical durability | 10000 cycles |
| Electrical durability | 2000 cycles IEC 60947-2 690 V In AC 50/60 Hz 4000 cycles IEC 60947-2 690 V In/2 AC 50/60 Hz 5000 cycles IEC 60947-2 440 V In AC 50/60 Hz 6000 cycles IEC 60947-2 440 V In/2 AC 50/60 Hz |
| Local signalling | Positive contact indication |
| [Icw] rated short-time withstand current | 19.2 kA |
| Neutral protection setting | Ir |
| Trip unit protection functions | LI |
| Protection type | Overload protection (long time) Instantaneous short-circuit protection |
| Long time pick-up adjustment type Ir | Adjustable |
| Long time pick-up adjustment range | 0.4...1 x In |
| Long time delay adjustment type | Adjustable 9 settings |
| [Tr] long-time delay adjustment range | 0.5...24 s 6 x Ir 0.7...16.6 s 7.2 x Ir 12.5...600 s 1.5 x Ir |
| Thermal memory | 20 mn |
| Instantaneous pick-up adjustment type Ii | Adjustable |
| Instantaneous pick-up adjustment range | 1.5...10 x Ir |
| Integral instant protection | 40 kA |
| Height | 327 mm |
| Width | 280 mm |
| Depth | 147 mm |
| Compatibility code | NS1000 |

Environment

| | |
|---------------------------------------|------------------------------|
| Standards | IEC 60947-2 |
| Product certifications | ASTA ASEFA |
| Power losses | 22 W |
| IP degree of protection | IP40 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to EN 50102 |
| Pollution degree | 3 conforming to IEC 60947 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -50...85 °C |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|