



### Main

Range of product	NS630b...1600
Device short name	SD
Product or component type	Auxiliary contact
Range compatibility	Compact Compact NS630b...1600
Offer type	C4
Signal contacts composition	1 NO/NC

### Complementary

Auxiliary contacts type	Low level
Mounting mode	Clip-on
[I <sub>th</sub> ] conventional free air thermal current	5 A
[I <sub>e</sub> ] rated operational current	Utilisation category DC-12 : 0.3 A network: DC at 250 V Utilisation category DC-12 : 0.6 A network: DC at 110 V Utilisation category DC-12 : 2.5 A network: DC at 48 V Utilisation category DC-14 : 0.03 A network: DC at 250 V Utilisation category DC-14 : 0.05 A network: DC at 110 V Utilisation category DC-14 : 0.2 A network: DC at 48 V Utilisation category DC-14 : 1 A network: DC at 24 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 110 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 220/240 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 250 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 380/440 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 48 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 480 V Utilisation category AC-15 : 0.1 A network: AC 50/60 Hz at 480 V Utilisation category AC-15 : 1.5 A network: AC 50/60 Hz at 380/440 V Utilisation category AC-15 : 2 A network: AC 50/60 Hz at 220/240 V Utilisation category AC-15 : 2.5 A network: AC 50/60 Hz at 110 V Utilisation category AC-15 : 3 A network: AC 50/60 Hz at 24 V Utilisation category AC-15 : 3 A network: AC 50/60 Hz at 48 V Utilisation category DC-12 : 5 A network: DC at 24 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 24 V
Minimum load	1 mA at 4 V DC

### Contractual warranty

Warranty period	18 months
-----------------	-----------