



### Main

Range	Compact
Range of product	NS1600b...3200
Product name	Compact NS
Product or component type	Basic frame
Device short name	Compact NS3200H
Device application	Distribution
Circuit breaker name	Compact NS3200H
Poles description	3P
Network type	AC
Breaking capacity code	H
Suitability for isolation	Yes conforming to IEC 60947-2
Utilisation category	Category B

### Complementary

Network frequency	50/60 Hz
Control type	Toggle
Mounting mode	Fixed
Mounting support	Backplate
Upside connection	Front
Downside connection	Front
[In] rated current	3200 A ( 50 °C )
[Ui] rated insulation voltage	800 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-2
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
Circuit breaker CT rating	3200 A
Breaking capacity	Icu 125 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 Icu 85 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 Icu 85 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2
[Ics] rated service breaking capacity	Ics 64 kA 380/415 V AC 50/60 Hz manual operation conforming to IEC 60947-2 Ics 64 kA 440 V AC 50/60 Hz manual operation conforming to IEC 60947-2 Ics 94 kA 220/240 V AC 50/60 Hz manual operation conforming to IEC 60947-2
Protection type	Without protection

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mechanical durability	5000 cycles conforming to IEC 60947-2
Electrical durability	1000 cycles 690 V AC 50/60 Hz In conforming to IEC 60947-2 2000 cycles 440 V AC 50/60 Hz In conforming to IEC 60947-2 2000 cycles 690 V AC 50/60 Hz In/2 conforming to IEC 60947-2 3000 cycles 440 V AC 50/60 Hz In/2 conforming to IEC 60947-2
Connection pitch	115 mm
[Icw] rated short-time withstand current	32 kA ( 3 s ) conforming to IEC 60947-2
Integral instant protection	130 kA
Height	350 mm
Width	420 mm
Depth	160 mm
Compatibility code	NS3200

## Environment

Standards	IEC 60947-2
Product certifications	ASEFA ASTA LCIE
Power losses	227 W
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Pollution degree	3 conforming to IEC 60947
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

## Contractual warranty

Warranty period	18 months
-----------------	-----------