



### Main

Range	Compact
Range of product	NS400...630 NS100...250
Product or component type	Trip unit
Range compatibility	Compact NS100...250 Compact NS400...630
Device application	Distribution
Poles description	4P
Protected poles description	4t 3t + N/2 3t
Neutral position	Left
Network type	AC
Network frequency	50/60 Hz
Trip unit name	STRAB
Trip unit technology	Electronic
Trip unit rating	216 A 70 °C 228 A 60 °C 240 A 20 °C
Protection type	Overload protection (long time) Short time short-circuit protection

### Complementary

Long time pick-up adjustment type Ir	Adjustable 48 settings
Long time pick-up adjustment range	0.4...1 x In
Long time delay adjustment type	Fixed
[Tr] long-time delay adjustment range	90...180 s at 1.5 x Ir 3.2...5 s at 7.2 x Ir 5...7.5 s at 6 x Ir
Short-time pick-up adjustment type I <sub>sd</sub>	Adjustable 8 settings
[I <sub>sd</sub> ] short-time pick-up adjustment range	2...10 x Ir
Short-time delay adjustment type	Fixed

34554

[Tsd] short-time delay adjustment range	0.04...0.06 s
[Tsd] short-time delay adjustment range	0.04...0.06 s
Instantaneous pick-up adjustment type li	Fixed
Display type	LED

## Environment

Standards	IEC 60947-2
Product certifications	ASTA ASEFA KEMA LCIE
IP degree of protection	IP40 conforming to IEC 60529
Pollution degree	3 conforming to IEC 60947
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

## Contractual warranty

Warranty period	18 months
-----------------	-----------