



Main

| | |
|---------------------------|-------------------------------|
| Range | Masterpact |
| Range of product | Masterpact NT |
| Product name | Masterpact NT |
| Product or component type | Basic frame |
| Device short name | Masterpact NT06 |
| Circuit breaker name | Masterpact NT06H2 |
| Poles description | 4P |
| Neutral position | Left |
| Network type | AC |
| Breaking capacity code | H2 |
| Suitability for isolation | Yes conforming to IEC 60947-2 |
| Utilisation category | Category B |

Complementary

| | |
|---|--|
| Network frequency | 50/60 Hz |
| Control type | Push-button |
| Mounting mode | Drawout |
| [In] rated current | 630 A (40 °C) |
| [Ui] rated insulation voltage | 1000 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 12 kV conforming to IEC 60947-2 |
| [Icm] rated short-circuit making capacity | 105 kA 220/415 V AC 50/60 Hz 105 kA 440 V AC 50/60 Hz 88 kA 525 V AC 50/60 Hz 88 kA 690 V AC 50/60 Hz |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Circuit breaker CT rating | 630 A |
| Breaking capacity | 50 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 50 kA Icu at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 42 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 42 kA Icu at 690 V AC 50/60 Hz conforming to IEC 60947-2 50 kA Icu at 380...415 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ics] rated service breaking capacity | Ics 50 kA 440 V AC 50/60 Hz conforming to IEC 60947-2 Ics 42 kA 525 V AC 50/60 Hz conforming to IEC 60947-2 Ics 42 kA 690 V AC 50/60 Hz conforming to IEC 60947-2 |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ics 50 kA 220/415 V AC 50/60 Hz conforming to IEC 60947-2

| | |
|--|--|
| Protection type | Without protection |
| Mechanical durability | 12500 cycles without maintenance conforming to IEC 60947-2 |
| Electrical durability | AC-23A : 3000 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 AC-23A : 6000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 AC-3 : 6000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 3000 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 6000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-2 |
| Connection pitch | 70 mm |
| [Icw] rated short-time withstand current | 20 kA (3 s) conforming to IEC 60947-2 42 kA (0.5 s) conforming to IEC 60947-2 42 kA (1 s) conforming to IEC 60947-2 |
| Integral instant protection | 81...99 kA |
| Maximum breaking time | 25 ms |
| Closing response time | < 50 ms |
| Height | 322 mm |
| Width | 358 mm |
| Depth | 276.5 mm |
| Compatibility code | NT06 |

Environment

| | |
|---------------------------------------|-----------------------------|
| Standards | IEC 60947-2 |
| Product certifications | ASEFA LCIE |
| Pollution degree | 3 conforming to IEC 60664-1 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...85 °C |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|