



Main

Range	Masterpact
Range of product	Masterpact NW
Product name	Masterpact NW
Product or component type	Switch disconnector
Device short name	Masterpact NW50
Switch-disconnector name	Masterpact NW50HA
Device application	Protection
Poles description	4P
Network type	AC
Network frequency	50/60 Hz
[Ie] rated operational current	5000 A AC 50/60 Hz 690 V
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to IEC 60947-3
[Uimp] rated impulse withstand voltage	12 kV conforming to IEC 60947-3
[Icm] rated short-circuit making capacity	187 kA 220...690 V AC 50/60 Hz
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-3
Breaking capacity code	HA
Suitability for isolation	Yes conforming to IEC 60947-3
Contact position indicator	Yes
Visible break	No
Pollution degree	4 conforming to IEC 60664-1

Complementary

Control type	Push-button
Mounting mode	Fixed
Operating rate	3 cyc/mn
[Icw] rated short-time withstand current	85 kA (1 s) conforming to IEC 60947-3 85 kA (3 s) conforming to IEC 60947-3
Mechanical durability	10000 cycles with maintenance conforming to IEC 60947-3 5000 cycles without maintenance conforming to IEC 60947-3
Electrical durability	AC-23A : 1500 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-3 AC-23A : 1500 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-3 AC-3 : 6000 cycles 440/690 V AC 50/60 Hz without maintenance conforming to IEC 60947-3

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Connection pitch	230 mm
Height	352 mm
Width	997 mm
Depth	297 mm
Product weight	160 kg
Targeted country	China
Compatibility code	NW50

Environment

Standards	IEC 60947-3
Product certifications	ASTA ASEFA
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-35...85 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------