



Main

Range of product	Masterpact NW Masterpact NW DC
Device short name	4 OF
Product or component type	Auxiliary contact
Range compatibility	Masterpact Masterpact NW
Signal contacts composition	4 NO/NC

Complementary

Auxiliary contacts type	Low level Standard
Mounting mode	Drawout
[Ie] rated operational current	Utilisation category AC-12 : 10 A network: AC 50/60 Hz at 240/380 V standard Utilisation category AC-12 : 10 A network: AC 50/60 Hz at 480 V standard Utilisation category AC-12 : 3 A network: AC 50/60 Hz at 380 V low level Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 24/48 V low level Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 240 V low level Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 690 V standard Utilisation category DC-12 : 10 A network: DC at 125 V standard Utilisation category DC-12 : 10 A network: DC at 24/48 V standard Utilisation category DC-12 : 3 A network: DC at 250 V low level Utilisation category DC-12 : 3 A network: DC at 250 V standard Utilisation category DC-12 : 6 A network: DC at 125 V low level Utilisation category DC-12 : 6 A network: DC at 24/48 V low level
Minimum load	100 mA at 24 V 2 mA at 15 V

Contractual warranty

Warranty period	18 months
-----------------	-----------

48468