



### Main

Range	Masterpact
Range of product	Masterpact NW corrosion protection
Product name	Masterpact NW
Product or component type	Basic frame
Device short name	Masterpact NW20
Circuit breaker name	Masterpact NW20H2
Poles description	3P
Network type	AC
Breaking capacity code	H2
Suitability for isolation	Yes conforming to IEC 60947-2
Utilisation category	Category B

### Complementary

Network frequency	50/60 Hz
Control type	Push-button
Mounting mode	Drawout
[In] rated current	2000 A ( 40 °C )
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	12 kV conforming to IEC 60947-2
[Icm] rated short-circuit making capacity	187 kA 525 V AC 50/60 Hz 187 kA 690 V AC 50/60 Hz
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
Circuit breaker CT rating	2000 A
Breaking capacity	100 kA Icu at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 100 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 85 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 100 kA Icu at 380...415 V AC 50/60 Hz conforming to IEC 60947-2
[Ics] rated service breaking capacity	Ics 85 kA 525 V AC 50/60 Hz conforming to IEC 60947-2 Ics 85 kA 690 V AC 50/60 Hz conforming to IEC 60947-2
Protection type	Without protection
Mechanical durability	10000 cycles without maintenance conforming to IEC 60947-2 20000 cycles with maintenance conforming to IEC 60947-2
Electrical durability	AC-23A : 6000 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-2

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

AC-23A : 8000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-2  
 AC-3 : 6000 cycles 440/690 V AC 50/60 Hz without maintenance conforming to IEC 60947-2  
 6000 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-2  
 8000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-2

Connection pitch	115 mm
[Icw] rated short-time withstand current	75 kA ( 3 s ) conforming to IEC 60947-2 85 kA ( 1 s ) conforming to IEC 60947-2
Integral instant protection	171...209 kA
Maximum breaking time	25 ms
Closing response time	< 70 ms
Height	439 mm
Width	441 mm
Depth	394.5 mm
Compatibility code	NW20

## Environment

Standards	IEC 60947-2
Product certifications	ASTA ASEFA
Pollution degree	4 conforming to IEC 60664-1
Anticorrosion treatment	With
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

## Contractual warranty

Warranty period	18 months
-----------------	-----------