



Main

Range	Masterpact
Range of product	Masterpact NW
Product name	Masterpact NW
Product or component type	Switch disconnector
Device short name	Masterpact NW16
Switch-disconnector name	Masterpact NW16HA
Device application	Protection
Poles description	3P
Network type	AC
Network frequency	50/60 Hz
[Ie] rated operational current	1600 A AC 50/60 Hz 1150 V
[Ui] rated insulation voltage	1250 V AC 50/60 Hz conforming to IEC 60947-3
[Uimp] rated impulse withstand voltage	12 kV conforming to IEC 60947-3
[Icm] rated short-circuit making capacity	105 kA 1150 V AC 50/60 Hz
[Ue] rated operational voltage	1150 V AC 50/60 Hz conforming to IEC 60947-3
Breaking capacity code	HA10
Suitability for isolation	Yes conforming to IEC 60947-3
Contact position indicator	Yes
Visible break	No
Pollution degree	3 conforming to IEC 60664-1

Complementary

Control type	Push-button
Mounting mode	Drawout
Mounting support	Chassis
Operating rate	3 cyc/mn
[Icw] rated short-time withstand current	50 kA (1 s) conforming to IEC 60947-3 50 kA (3 s) conforming to IEC 60947-3
Mechanical durability	12500 cycles without maintenance conforming to IEC 60947-3 25000 cycles with maintenance conforming to IEC 60947-3
Electrical durability	AC-23A : 10000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-3

AC-23A : 10000 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-3
AC-3 : 6000 cycles 440/690 V AC 50/60 Hz without maintenance conforming to IEC 60947-3

Connection pitch	115 mm
Height	352 mm
Width	442 mm
Depth	297 mm
Product weight	90 kg
Compatibility code	NW16

Environment

Standards	IEC 60947-3
Product certifications	ASEFA ASTA
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-35...85 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------