



Main

Range of product	INF100...160
Range	Fupact
Product name	Fupact INF
Device short name	INFC125
Product or component type	Switch-disconnector-fuse
Device application	Protection
Poles description	4P
Protected poles description	4f
Fuse type	NFC
Fuse size	22 x 58 mm
Network type	DC AC
Network frequency	50/60 Hz

Complementary

Control type	Without handle
Rotary handle mounting location	Front
Rotary handle mounting style	Direct Extended
Mounting support	Mounting plate DIN rail with specific accessories
[Ie] rated operational current	AC-23A : 125 A AC 50/60 Hz 380/415 V DC-23A : 125 A DC 125 V 2 poles in series AC-23A : 125 A AC 50/60 Hz 500/525 V AC-22A : 125 A AC 50/60 Hz 380/415 V DC-23A : 125 A DC 500 V 4 poles in series AC-22A : 125 A AC 50/60 Hz 500/525 V AC-22A : 125 A AC 50/60 Hz 220/240 V AC-23B : 125 A AC 50/60 Hz 660/690 V AC-22A : 125 A AC 50/60 Hz 660/690 V AC-23A : 125 A AC 50/60 Hz 220/240 V DC-22A : 125 A DC 125 V 2 poles in series AC-22A : 125 A AC 50/60 Hz 440/480 V DC-22A : 125 A DC 500 V 4 poles in series AC-23A : 125 A AC 50/60 Hz 440/480 V DC-23A : 125 A DC 250 V 2 poles in series DC-22A : 125 A DC 250 V 2 poles in series

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

[Ith] conventional free air thermal current	100 A (60 °C) vertical 103 A (50 °C) horizontal 106 A (55 °C) vertical 109 A (45 °C) horizontal 113 A (50 °C) vertical 115 A (40 °C) horizontal 119 A (45 °C) vertical 121 A (35 °C) horizontal 125 A (40 °C) power dissipation per fuse: 12 W 125 A (40 °C) vertical 81 A (70 °C) horizontal 86 A (65 °C) horizontal 88 A (70 °C) vertical 92 A (60 °C) horizontal 94 A (65 °C) vertical 97 A (55 °C) horizontal
[Ithe] conventional enclosed thermal current	125 A (40 °C) / Power dissipation per fuse: 12 W 300 mm x 350 mm x 200 mm
Maximum power	110 kW 660/690 V AC 50/60 Hz 37 kW 220/240 V AC 50/60 Hz 60 kW 380/400 V AC 50/60 Hz 60 kW 415 V AC 50/60 Hz 80 kW 500/525 V AC 50/60 Hz
Rated duty	Uninterrupted
Intermittent duty class	Class 120 - 60 %
[Ui] rated insulation voltage	1000 V AC 50/60 Hz 1000 V DC
[Uimp] rated impulse withstand voltage	12 kV
[Ue] rated operational voltage	500 V DC 690 V AC 50/60 Hz 690 V AC 50/60 Hz AC-20 690 V DC DC-20
[Im] rated making and breaking capacity	Icm 105 kA conforming to DIN 690 V with fuse Icm 15 kA 690 V without fuse Icm 176 kA conforming to BS 415 V with fuse Icm 22 kA 415 V without fuse Icm 22 kA 500 V without fuse Icm 220 kA conforming to DIN 500 V with fuse Icn 100 kA conforming to DIN 500 V with fuse Icn 50 kA conforming to DIN 690 V with fuse Icn 80 kA conforming to BS 415 V with fuse
Suitability for isolation	Yes
Contact position indicator	Yes
Contact operation	Double-break

Environment

Mechanical durability	10000 cycles
Electrical durability	AC-22A : 1500 cycles 500 V AC 50/60 Hz AC-22A : 1500 cycles 690 V AC 50/60 Hz AC-23A : 1500 cycles 500 V AC 50/60 Hz AC-23A : 1500 cycles 690 V AC 50/60 Hz
[Icw] rated short-time withstand current	5 kA (1 s) 0.95 kA (30 s) 1.15 kA (20 s) 2.9 kA (3 s)
Design	Horizontal design
Tightening torque	Terminal : 15...22 N.m
Height	140 mm
Width	215 mm
Depth	130 mm
Standards	EN/IEC 60947-5 EN/IEC 60269-1 EN/IEC 60947-1 EN/IEC 60269-4 EN/IEC 60947-3

Product certifications	KEMA-KEUR
IP degree of protection	IP20 conforming to IEC 60529 IP65 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102 IK10 conforming to EN 50102
Pollution degree	3
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C
Compatibility code	INF100...160

Contractual warranty

Warranty period	18 months
-----------------	-----------

Product Life Status	END-OF-SALE NOTICE
---------------------	--------------------

49526