



### Main

Range of product	INF200...800
Range	Fupact
Product name	Fupact INF
Device short name	INFB250
Product or component type	Switch-disconnector-fuse
Device application	Protection
Poles description	4P
Protected poles description	3f
Fuse type	BS
Fuse size	B1 B3 B2
Network type	AC DC
Network frequency	50/60 Hz

### Complementary

Control type	Rotary handle
Rotary handle mounting location	Lateral
Rotary handle mounting style	Extended
Handle colour	Black
Handle front plate colour	Black
Provision for padlocking	3 padlocks
Mounting support	Mounting plate
[Ie] rated operational current	AC-23A : 250 A AC 50/60 Hz 220/240 V AC-22A : 250 A AC 50/60 Hz 440/480 V AC-23A : 250 A AC 50/60 Hz 500/525 V AC-22A : 250 A AC 50/60 Hz 220/240 V DC-23A : 250 A DC 750 V 3 poles in series AC-22A : 250 A AC 50/60 Hz 500/525 V AC-23A : 250 A AC 50/60 Hz 380/415 V AC-22A : 250 A AC 50/60 Hz 380/415 V DC-22A : 250 A DC 125 V 2 poles in series DC-22A : 250 A DC 500 V 3 poles in series DC-22A : 250 A DC 250 V 2 poles in series AC-23A : 250 A AC 50/60 Hz 440/480 V

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

DC-23A : 250 A DC 125 V 2 poles in series  
 AC-23A : 250 A AC 50/60 Hz 660/690 V  
 DC-22A : 250 A DC 750 V 3 poles in series  
 AC-22A : 250 A AC 50/60 Hz 660/690 V  
 DC-23A : 250 A DC 500 V 3 poles in series  
 DC-23A : 250 A DC 250 V 2 poles in series

[Ith] conventional free air thermal current	161 A ( 70 °C ) horizontal 172 A ( 65 °C ) horizontal 175 A ( 70 °C ) vertical 184 A ( 60 °C ) horizontal 187 A ( 65 °C ) vertical 195 A ( 55 °C ) horizontal 200 A ( 60 °C ) vertical 207 A ( 50 °C ) horizontal 212 A ( 55 °C ) vertical 218 A ( 45 °C ) horizontal 225 A ( 50 °C ) vertical 230 A ( 40 °C ) horizontal 237 A ( 45 °C ) vertical 242 A ( 35 °C ) horizontal 250 A ( 40 °C ) power dissipation per fuse: 32 W 250 A ( 40 °C ) vertical
[Ithe] conventional enclosed thermal current	230 A ( 40 °C ) / Power dissipation per fuse: 27 W 600 mm x 350 mm x 300 mm 250 A ( 40 °C ) / Power dissipation per fuse: 23 W 600 mm x 350 mm x 300 mm
Maximum power	132 kW 380/400 V AC 50/60 Hz 140 kW 415 V AC 50/60 Hz 170 kW 500/525 V AC 50/60 Hz 230 kW 660/690 V AC 50/60 Hz 70 kW 220/240 V AC 50/60 Hz
Rated duty	Uninterrupted
Intermittent duty class	Class 120 - 60 %
[Ui] rated insulation voltage	1000 V AC 50/60 Hz 1000 V DC
[Uimp] rated impulse withstand voltage	12 kV
[Ue] rated operational voltage	1000 V AC 50/60 Hz AC-20 1000 V DC DC-20 690 V AC 50/60 Hz 750 V DC
[Im] rated making and breaking capacity	Icm 105 kA conforming to DIN 690 V with fuse Icm 176 kA conforming to BS 415 V with fuse Icm 220 kA conforming to DIN 500 V with fuse Icm 35 kA 690 V without fuse Icm 40 kA 415 V without fuse Icm 40 kA 500 V without fuse Icn 100 kA conforming to DIN 500 V with fuse Icn 50 kA conforming to DIN 690 V with fuse Icn 80 kA conforming to BS 415 V with fuse
Suitability for isolation	Yes
Contact position indicator	Yes
Contact operation	Double-break

## Environment

Mechanical durability	8000 cycles
Electrical durability	AC-22A : 1000 cycles 500 V AC 50/60 Hz AC-22A : 1000 cycles 690 V AC 50/60 Hz AC-23A : 1000 cycles 500 V AC 50/60 Hz AC-23A : 1000 cycles 690 V AC 50/60 Hz
[Icw] rated short-time withstand current	8 kA ( 1 s ) 1.5 kA ( 30 s ) 1.8 kA ( 20 s ) 4.65 kA ( 3 s )
Design	Horizontal design
Tightening torque	Terminal : 30...44 N.m
Height	232 mm
Width	340 mm
Depth	199 mm

Standards	EN/IEC 60947-1 EN/IEC 60947-5 EN/IEC 60947-3 EN/IEC 60269-1 EN/IEC 60269-4
Product certifications	KEMA-KEUR
IP degree of protection	IP20 conforming to IEC 60529 IP65 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102 IK10 conforming to EN 50102
Pollution degree	3
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C
Compatibility code	INF200...800

### Contractual warranty

Warranty period	18 months
-----------------	-----------

Product Life Status	END-OF-SALE NOTICE
---------------------	--------------------

49592