



### Main

Range of product	ISFT160
Range	Fupact
Product name	Fupact ISFT
Device short name	ISFT160
Product or component type	Fuse-switch disconnecter
Device application	Distribution Equipment protection, monitoring and control

### Complementary

Poles description	3P
Protected poles description	3f
Fuse type	DIN
Fuse size	NH00 NH000
Network type	AC DC
Network frequency	50/60 Hz
Control type	Fuse carriers handle
[I <sub>th</sub> ] conventional free air thermal current	112 A ( 70 °C ) horizontal 112 A ( 70 °C ) vertical 120 A ( 65 °C ) horizontal 120 A ( 65 °C ) vertical 128 A ( 60 °C ) horizontal 128 A ( 60 °C ) vertical 136 A ( 55 °C ) horizontal 136 A ( 55 °C ) vertical 144 A ( 50 °C ) horizontal 144 A ( 50 °C ) vertical 152 A ( 45 °C ) horizontal 152 A ( 45 °C ) vertical 160 A ( 40 °C ) power dissipation per fuse: 12 W 160 A ( 40 °C ) horizontal 160 A ( 40 °C ) vertical
[I <sub>th</sub> ] conventional enclosed thermal current	160 A ( 40 °C ) / Power dissipation per fuse: 12 W
Rated duty	Uninterrupted
[U <sub>i</sub> ] rated insulation voltage	800 V AC 50/60 Hz

	800 V DC
[Uimp] rated impulse withstand voltage	8 kV
[Ue] rated operational voltage	440 V DC 690 V AC 50/60 Hz 800 V AC 50/60 Hz AC-20 800 V DC DC-20
[Ie] rated operational current	100 A AC-21B 660/690 V AC 50/60 Hz 160 A AC-21B 220/240 V AC 50/60 Hz 160 A AC-21B 380/415 V AC 50/60 Hz 160 A AC-22B 220/240 V AC 50/60 Hz 160 A AC-22B 380/415 V AC 50/60 Hz 160 A AC-21B 440/480 V AC 50/60 Hz 160 A AC-21B 500 V AC 50/60 Hz 160 A DC-21B 125 V DC 1 pole 160 A DC-21B 220 V DC 1 pole 160 A DC-21B 440 V DC 2 poles in series
[Im] rated making and breaking capacity	Icm 105 kA 415 V Icm 105 kA 500 V Icm 105 kA 690 V Icn 50 kA 415 V Icn 50 kA 500 V Icn 50 kA 690 V
Suitability for isolation	Yes
Visible break	Yes
Contact operation	Single-break
Mechanical durability	1600 cycles
Electrical durability	200 cycles 690 V AC 50/60 Hz AC-21B 200 cycles 415 V AC 50/60 Hz AC-22B
Provision for padlocking	3 padlocks
Mounting support	Busbars
Mounting support	Busbars
Mounting location	Side by side
Design	Horizontal design
Connections terminals	Hook-on
Connections - terminals	Hook-on 160 A busbar 60 mm
Tightening torque	Terminal : 4 N.m

## Environment

Height	163 mm
Width	107 mm
Depth	80 mm
Standards	EN/IEC 60947-1 EN/IEC 60947-3 IEC 60269-2-1
Product certifications	KEMA-KEUR
IP degree of protection	IP20 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Pollution degree	3 conforming to IEC 60947
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C
Compatibility code	ISFT160

## Offer Sustainability

REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
-------	--

## Contractual warranty

Warranty period	18 months
-----------------	-----------