



### Main

Range of product	ISFT250...630
Range	Fupact
Product name	Fupact ISFT
Device short name	ISFT400
Product or component type	Fuse-switch disconnector
Device application	Distribution Equipment protection, monitoring and control

### Complementary

Poles description	3P
Protected poles description	3f
Fuse type	DIN
Fuse size	NH2
Network type	AC DC
Network frequency	50/60 Hz
Control type	Fuse carriers handle
[I <sub>th</sub> ] conventional free air thermal current	280 A ( 70 °C ) horizontal 280 A ( 70 °C ) vertical 300 A ( 65 °C ) horizontal 300 A ( 65 °C ) vertical 320 A ( 60 °C ) horizontal 320 A ( 60 °C ) vertical 340 A ( 55 °C ) horizontal 340 A ( 55 °C ) vertical 360 A ( 50 °C ) horizontal 360 A ( 50 °C ) vertical 380 A ( 45 °C ) horizontal 380 A ( 45 °C ) vertical 400 A ( 40 °C ) power dissipation per fuse: 34 W 400 A ( 40 °C ) horizontal 400 A ( 40 °C ) vertical
[I <sub>th</sub> e] conventional enclosed thermal current	400 A ( 40 °C ) / Power dissipation per fuse: 34 W
Rated duty	Uninterrupted
[U <sub>i</sub> ] rated insulation voltage	800 V AC 50/60 Hz 800 V DC

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

[Uimp] rated impulse withstand voltage	8 kV
[Ue] rated operational voltage	440 V DC 690 V AC 50/60 Hz 800 V AC 50/60 Hz AC-20 800 V DC DC-20
[Ie] rated operational current	400 A AC-21B 220/240 V AC 50/60 Hz 400 A AC-21B 380/415 V AC 50/60 Hz 400 A AC-21B 440/480 V AC 50/60 Hz 400 A AC-21B 500 V AC 50/60 Hz 400 A AC-21B 660/690 V AC 50/60 Hz 400 A AC-22B 220/240 V AC 50/60 Hz 400 A AC-22B 380/415 V AC 50/60 Hz 400 A DC-21B 125 V DC 1 pole 400 A DC-21B 220 V DC 1 pole 400 A DC-21B 440 V DC 2 poles in series
[Im] rated making and breaking capacity	Icm 105 kA 415 V Icm 105 kA 500 V Icm 105 kA 690 V Icn 50 kA 415 V Icn 50 kA 500 V Icn 50 kA 690 V
Suitability for isolation	Yes
Visible break	Yes
Contact operation	Single-break
Mechanical durability	1000 cycles
Electrical durability	200 cycles 690 V AC 50/60 Hz AC-21B 200 cycles 415 V AC 50/60 Hz AC-22B
Provision for padlocking	3 padlocks
Mounting support	Busbars
Mounting support	Busbars
Mounting location	Side by side
Design	Horizontal design
Connections terminals	Hook-on
Connections - terminals	Hook-on 400 A busbar 60 mm

## Environment

Height	271 mm
Width	210 mm
Depth	127 mm
Standards	EN/IEC 60947-1 EN/IEC 60947-3 IEC 60269-2-1
Product certifications	KEMA-KEUR
IP degree of protection	IP20 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Pollution degree	3 conforming to IEC 60947
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C
Compatibility code	ISFT250...630

## Contractual warranty

Warranty period	18 months
-----------------	-----------