



Main

Range of product	ConneXium
Product or component type	Ethernet TCP/IP unmanaged switch
Concept	Transparent Ready
Communication port protocol	Ethernet TCP/IP
Port Ethernet	100BASE-FX - 1 port(s) fiber optic 10BASE-T/100BASE-TX - 4 port(s) copper cable
Maximum number of switches in cascade	Unlimited

Complementary

Integrated connection type	SC fiber optic Shielded RJ45 copper cable
Transmission support medium	Twisted shielded pairs cable CAT 5E for copper cable Single mode optical fiber for fiber optic
Cable distance between devices	100 m copper cable
Optic fiber length	9/125 μm
Attenuation	16 dB 9/125 μm
Redundancy	P1 and P2 redundant power supplies
[Us] rated supply voltage	24 V
Supply voltage limits	18...32 V DC SELV
Power consumption in W	5.4 W
Electrical connection	Removable connector 5 ways power supply
Mounting support	35 mm symmetrical DIN rail
Marking	CE
Local signalling	1 LED fault 1 LED per channel Ethernet link active 2 LEDs P1 P2 power supplies
Alarm output	1 voltfree contact ≤ 1 A
Alarm function	Switch fault Data link status Power supply fault
Ethernet cabling system	TF switches
Current consumption	≤ 200 mA 24 V DC
Width	47 mm

Height	135 mm
Depth	111 mm
Product weight	0.33 kg

Environment

Ambient air temperature for operation	0...60 °C
Relative humidity	0...95 % without condensation
IP degree of protection	IP20
Standards	CSA C22.2 No 142 CUL 60950 CSA C22.2 No 213 Class I Division 2 UL 1604 UL 508


Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0619 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
Product environmental profile	Available Product environmental

Contractual warranty

Warranty period	18 months
-----------------	-----------

Power Wiring



499NSS25101