

Window-type current transformer, Class 1 400 A/5 A, 5 VA

Model	
Product brand name	SENTRON
Product designation	Window-type current transformers
Operating apparent output / rated value	5 V·A
Reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	T
Protection class	
Protection class IP	IP20
<ul style="list-style-type: none"> Ratio of input current/output current 	400/5 A
<ul style="list-style-type: none"> Current / at output / rated value 	5 A
<ul style="list-style-type: none"> Current / at input / rated value 	400 A
Accuracy class / of the current transformer	class 1
Product feature / Touch protection	Yes
Connections	
Type of electrical connection / at output	screw-type terminals
Mechanical Design	
Height	85.5 mm
Width	64 mm
Width <ul style="list-style-type: none"> of the push-through bus bar / at 1 bus bar / maximum of the push-through bus bar / in case of 2 bus bars / maximum 	30 mm 25 mm
Depth	80 mm
Mounting type	screw fixing
Outer diameter / of the push-through conductor / maximum	28 mm
Environmental conditions	
Ambient temperature <ul style="list-style-type: none"> during operation / minimum during operation / maximum 	-10 °C 55 °C
Certificates	
Reference code / acc. to DIN EN 61346-2	T
Further information	

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4NC5225-2CE20>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4NC5225-2CE20>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4NC5225-2CE20

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>