



### Main

Range of product	Varpact Classic
Device short name	Varpact
Network frequency	50 Hz
Capacitor technology	3P capacitor
Reactive power rating	120 kvar for 400 V AC 50 Hz slightly polluted
Module type	Single step
Number of steps	1 x 120 kvar
Network rated voltage	400 V AC 50 Hz 415 V AC 50 Hz
Network pollution level	Slightly polluted ( 0...15 % ) at 400 V 50 Hz
[Ui] rated insulation voltage	690 V AC 50 Hz
Mounting location	In stand-alone cubicles Inside main low voltage switchboard

### Complementary

Device wiring	Cable 35 kA
Capacitor voltage	415 V AC 50 Hz
Power losses	<= 1.9 W/kVAr maximum current
Capacitance tolerance	- 5 % to 10 %
Rated short-duration power frequency withstand voltage	3 kV 50 Hz 1 minute
Maximum permissible voltage	1.1 x Un 8 hours over 24 hours conforming to IEC 60831
[Imp] maximum permanent current	1.3 x I1 400 V
Colour code	( RAL 7016 )
Height	374 mm
Width	565 mm
Depth	231 mm
Product weight	16 kg
Compatibility code	CAPACITOR_VARPACT_CLASSIC

### Environment

Standards	IEC 60439-1
-----------	-------------

IEC 61921  
EN 60439-1

---

Ambient air temperature for operation	-5...40 °C
Average ambient air temperature for operation	25 °C ( average over 1 year ) 35 °C ( average over 24 hours )

---

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---

Product Life Status

END-OF-SALE NOTICE