



Main

Range	Vigirex
Range of product	Vigirex
Device short name	RH197P
Product or component type	Residual current protection relay
Range compatibility	Vigirex RH TOA earth leakage current sensor Vigirex RH A earth leakage current sensor
Relay application	Residual current protection relay

Complementary

Earthing system	TN-S IT TT
[Us] rated supply voltage	380...415 V AC at 50/60 Hz
Power consumption in VA	4 VA
Type of measurement	Earth fault current internal measurement - 7...7 %
Refresh time	0.5 s
Alarm threshold	1
Residual earth-leakage time delay adjustment type	Instantaneous 0.03 A Adjustable 7 settings 0.03...30 A 0...4.5 s
Signal contacts composition	1 NO
Test function	Remote test Local
Monitoring	Electronics (watchdog) Power supply (continuous) Relay/Sensor link (continuous)
[I _{th}] conventional enclosed thermal current	8 A
Minimum load	10 mA at 12 V
Product weight	0.3 kg
Mechanical robustness	IK protection 2 joules IK07 conforming to EN 50102 IP protection IP20 conforming to IEC 60529 IP protection IP30 conforming to IEC 60529 IP protection IP40 conforming to IEC 60529 Vibrations 13.2...100 Hz 0.7 g Vibrations 2...13.2 Hz +/- 1 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Fire resistance conforming to IEC 60695-2-1

Earth-leakage protection class	Class A si Class AC
Overtoltage category	IV
Tamperproof of settings	Protected by sealable cover
Mounting support	Panel
Height	72 mm
Width	72 mm
Depth	92 mm
Connections - terminals	Terminal block auxiliary power supply 0.2...2.5 mm ² flexible AWG 24...AWG 12 Terminal block auxiliary power supply 0.2...2.5 mm ² rigid AWG 24...AWG 12 Terminal block fault 0.2...2.5 mm ² flexible AWG 24...AWG 12 Terminal block fault 0.2...2.5 mm ² rigid AWG 24...AWG 12 Terminal block relay test and fault reset 0.2...2.5 mm ² flexible AWG 24...AWG 12 Terminal block relay test and fault reset 0.2...2.5 mm ² rigid AWG 24...AWG 12 Terminal block sensor 0.2...2.5 mm ² flexible AWG 24...AWG 12 Terminal block sensor 0.2...2.5 mm ² rigid AWG 24...AWG 12 Terminal block voltage presence 0.2...2.5 mm ² flexible AWG 24...AWG 12 Terminal block voltage presence 0.2...2.5 mm ² rigid AWG 24...AWG 12 Terminal block auxiliary power supply 0.25...2.5 mm ² flexible AWG 24...AWG 12 Terminal block fault 0.25...2.5 mm ² flexible AWG 24...AWG 12 Terminal block relay test and fault reset 0.25...2.5 mm ² flexible AWG 24...AWG 12 Terminal block sensor 0.25...2.5 mm ² flexible AWG 24...AWG 12 Terminal block voltage presence 0.25...2.5 mm ² flexible AWG 24...AWG 12
Wire stripping length	Fault : 7 mm Sensor : 7 mm Voltage presence : 7 mm Auxiliary power supply : 7 mm Relay test and fault reset : 7 mm
Tightening torque	Auxiliary power supply : 0.6 N.m Fault : 0.6 N.m Relay test and fault reset : 0.6 N.m Sensor : 0.6 N.m Voltage presence : 0.6 N.m
Compatibility code	RH197P

Environment

Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...85 °C
Electromagnetic compatibility	Conducted and radiated emissions : B conforming to CISPR 11 Conducted radio-frequency immunity test : 3 conforming to IEC 61000-4-6 Electrostatic discharge immunity test : 4 conforming to IEC 61000-4-2 High-energy conducted susceptibility : 4 conforming to IEC 61000-4-5 Low-energy conducted susceptibility : 4 conforming to IEC 61000-4-4 Radiated susceptibility : 3 conforming to IEC 61000-4-3
Electrical shock protection class	Class II

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0937 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------