



Main

Range of product	Sepam series 80 Sepam series 20 Sepam series 48 Sepam series 60 Sepam series 40 Sepam series 80 NPP
Device short name	ACE959

Complementary

Communication port protocol	Modbus RTU network: E-LAN interface: RS485 - 4-wire Modbus RTU network: S-LAN interface: RS485 - 4-wire
Local signalling	LED for link activity on front face
[Us] rated supply voltage	12 V DC tolerance: +/- 10 % 24 V DC tolerance: +/- 10 %
Supply current	40 mA : maximum in sending mode 16 mA : receiving mode
Mounting mode	Fixed
Mounting support	Symmetrical DIN rail
Height	88 mm
Width	144 mm
Depth	30 mm
Product weight	0.2 kg
Mechanical robustness	Earthquakes in operation (level: 2) : 1 Gn (vertical axes) conforming to IEC 60255-21-3 Earthquakes in operation (level: 2) : 2 Gn (horizontal axes) conforming to IEC 60255-21-3 Jolts de-energized (level: 2) : 20 Gn/16 ms conforming to IEC 60255-21-2 Shocks de-energized (level: 2) : 27 Gn/11 ms conforming to IEC 60255-21-2 Shocks in operation (level: 2) : 10 Gn/11 ms conforming to IEC 60255-21-2 Vibrations de-energized (level: 2) : 2 Gn, 10 Hz...150 Hz conforming to IEC 60255-21-1 Vibrations in operation (level: 2) : 1 Gn, 10 Hz...150 Hz conforming to IEC 60255-21-1 Vibrations in operation (level: Fc) : 2 Hz...13.2 Hz, a = +/- 1 mm conforming to IEC 60068-2-6
Cable distance between devices	10 Devices 180 m cable length at 12 V DC 10 Devices 750 m cable length at 24 V DC 20 Devices 160 m cable length at 12 V DC


	20 Devices 450 m cable length at 24 V DC 25 Devices 125 m cable length at 12 V DC 25 Devices 375 m cable length at 24 V DC 5 Devices 1000 m cable length at 24 V DC 5 Devices 320 m cable length at 12 V DC
Auxiliary connection terminal	Earthing terminal : screw-type connector tinned copper braid 6...100 mm ² Earthing terminal : screw-type connector cable 2.5...50 mm ² 0.2 m
Tightening torque	Earthing terminal : 2.2 N.m

Environment

Electromagnetic compatibility	1 MHz damped oscillating wave immunity tests-conducted disturbances (2.5 kV CM, 1 kV DM) conforming to IEC 60255-22-1 1 MHz damped oscillating wave immunity tests-conducted disturbances (2.5 kV CM, 2.5 kV DM) conforming to ANSI C37.90.1 100 kHz damped oscillating wave immunity tests-conducted disturbances (2.5 kV CM, 1 kV DM) conforming to IEC 61000-4-12 Conducted disturbance emission tests conforming to IEC 60255-25 Conducted disturbance emission tests: A conforming to EN 55022 Disturbing field emission tests conforming to IEC 60255-25 Disturbing field emission tests: A conforming to EN 55022 Electrostatic discharge immunity tests-radiated disturbances (8 kV air, 4 kV contact) conforming to ANSI C37.90.3 Electrostatic discharge immunity tests-radiated disturbances (8 kV air, 6 kV contact) conforming to IEC 60255-22-2 Fast transient bursts immunity tests-conducted disturbances (4kV, 2.5 kHz) conforming to ANSI C37.90.1 Fast transient bursts immunity tests-conducted disturbances: A and B (4kV, 2.5 kHz/2 kV, 5 kHz) conforming to IEC 60255-22-4 Fast transient bursts immunity tests-conducted disturbances: IV (4kV, 2.5 kHz) conforming to IEC 61000-4-4 Immunity to conducted RF disturbances immunity tests-conducted disturbances: III (10 V) conforming to IEC 60255-22-6 Immunity to magnetic fields at network frequency immunity tests-radiated disturbances: IV (30 A/m (continuous)-300 A/m (1-3 s)) conforming to IEC 61000-4-8 Immunity to radiated fields immunity tests-radiated disturbances (10 V/m, 80 MHz...1 GHz) conforming to IEC 60255-22-3 Immunity to radiated fields immunity tests-radiated disturbances (35 V/m, 25 MHz...1 GHz) conforming to ANSI C37.90.2 Immunity to radiated fields immunity tests-radiated disturbances: III (10 V/m, 80 MHz...2 GHz) conforming to IEC 61000-4-3 Surges immunity tests-conducted disturbances: III (2 kV CM, 1 kV DM) conforming to IEC 61000-4-5 Voltage interruptions immunity tests-conducted disturbances (100 % during 100 ms) conforming to IEC 60255-11
Climatic withstand	Exposure to cold (in operation) : Ad: - 25 °C conforming to IEC 60068-2-1 Exposure to dry heat (in operation) : Bd: 70 °C conforming to IEC 60068-2-2 Continuous exposure to damp heat (in operation) : Cab: 10 days, 93 % RH, 40 °C conforming to IEC 60068-2-78 Salt mist (in operation) : Kb/2: 6 days conforming to IEC 60068-2-52 Influence of corrosion/gaz test 2 (in operation) : 21 days, 75 % RH, 25 °C, 0.5 ppm H2S, 1 ppm SO2 conforming to IEC 60068-2-60 Influence of corrosion/gaz test 4 (in operation) : 21 days, 75 % RH, 25 °C, 0.01 ppm H2S, 0.2 ppm SO2, 0.2 ppm NO2, 0.01 ppm Cl2 conforming to IEC 60068-2-60 Temperature variation with specified variation rate (in storage) : Nb: - 25 °C to 70 °C, 5 °C/min conforming to IEC 60068-2-14 Exposure to cold (in storage) : Ab: - 25 °C conforming to IEC 60068-2-1 Exposure to dry heat (in storage) : Bb: 70 °C conforming to IEC 60068-2-2 Continuous exposure to damp heat (in storage) : Cab: 56 days, 93 % RH, 40 °C conforming to IEC 60068-2-78 Continuous exposure to damp heat (in storage) : Db: 6 days, 95 % RH, 55 °C conforming to IEC 60068-2-30
Ambient air temperature for operation	-25...70 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0925 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Product environmental profile	Available  Product environmental
Product end of life instructions	Available

59643