



Main

| | |
|---|---|
| Range of product | GFP |
| Range | Multi 9 |
| Product name | Multi 9 GFP |
| Product or component type | Residual current circuit breaker (RCCB) |
| Device short name | GFP |
| Poles description | 4P |
| Neutral position | Left |
| [In] rated current | 25 A 40 °C |
| Network type | AC |
| Earth-leakage sensitivity | 30 mA |
| Earth-leakage protection time delay | Instantaneous |
| Earth-leakage protection class | Type AC-SIE |
| Rated conditional short-circuit current | 10 kA |
| Utilisation category | AC-23A |

Complementary

| | |
|--|---|
| Network frequency | 50/60 Hz |
| [Ue] rated operational voltage | 240 V AC 60 Hz 480Y/277 V AC 60 Hz 230/400 V AC 50 Hz 240/415 V AC 50 Hz |
| [Uimp] rated impulse withstand voltage | 6 kV |
| Control type | Toggle |
| Local signalling | Fault indication |
| Connection pitch | 18 mm : Between phases |
| 9 mm pitches | 8 |
| Height | 81 mm |
| Width | 72 mm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|-----------------------------|---|
| Depth | 75 mm |
| Embedding depth | 75 mm |
| Product weight | 450 g |
| Colour | Grey |
| Mechanical durability | 20000 cycles |
| Provision for padlocking | Padlockable |
| Locking options description | Padlocking in OFF position |
| Connections - terminals | Tunnel type terminals 2.5...35 mm ² flexible Tunnel type terminals 2.5...35 mm ² rigid |
| Tightening torque | 3.5 N.m |
| Compatibility code | GFP |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 61008 UL 1053 |
| IP degree of protection | IPxx B conforming to IEC 60529 IP20 conforming to IEC 60529 IP40 conforming to IEC 60529 |
| Tropicalisation | 2 |
| Relative humidity | 95 % (55 °C) |
| Ambient air temperature for operation | -25...60 °C |
| Ambient air temperature for storage | -40...70 °C |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0844 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product environmental |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|