



## Main

Range	Masterpact
Range of product	Masterpact NW
Product name	Masterpact NW UL 489
Product or component type	Basic frame
Device short name	Masterpact NW16
Circuit breaker name	Masterpact NW16N
Poles description	4P
Neutral position	Left
Network type	AC
Breaking capacity code	N

## Complementary

Network frequency	50/60 Hz
Control type	Push-button
Mounting mode	Drawout
[In] rated current	1600 A
[Ue] rated operational voltage	240...600 V AC 50/60 Hz
Breaking capacity	65 kA at 480 V AC 50/60 Hz conforming to IEC 60947-2 50 kA at 600 V AC 50/60 Hz conforming to IEC 60947-2 65 kA at 240 V AC 50/60 Hz conforming to IEC 60947-2
Protection type	Without protection
Connection pitch	115 mm
[Icw] rated short-time withstand current	65 kA ( 1 s )
Integral instant protection	40 kA
Maximum breaking time	30 ms
Closing response time	<= 70 ms
Height	439 mm
Width	556 mm
Depth	394.5 mm
Compatibility code	NW16

64654

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

**Environment**

---

Standards	UL 489
IP degree of protection	IP30

---

**Contractual warranty**

---

Warranty period	18 months
-----------------	-----------

---