



Main

| | |
|-------------------------------|--|
| Range of product | VarSet |
| Device short name | Varset Harmony |
| Device presentation | Cubicle A4B |
| Network frequency | 50 Hz |
| Capacitor technology | 3P capacitor |
| Reactive power rating | 500 kvar for 400 V AC 50 Hz |
| Number of steps | 10 x 50 kvar |
| Network rated voltage | 400 V AC 50 Hz 415 V AC 50 Hz |
| Network pollution level | Highly polluted (25...50 %) at 400 V |
| [Ui] rated insulation voltage | 690 V |

Complementary

| | |
|--|--|
| Device composition | Circuit-breaker equipment protection Contactor Controller equipment regulation Detuned reactors Incoming circuit-breaker equipment protection Varplus ² capacitors |
| Device wiring | Cables |
| Internal voltage transformer | 400/230 V |
| Capacitor voltage | 480 V AC 50 Hz |
| Tuning order | 4.3 - 215 Hz |
| Capacitance tolerance | - 5 % to 10 % |
| Rated short-duration power frequency withstand voltage | 2.5 kV 50 Hz 1 minute |
| Maximum permissible voltage | 1.1 x Un |
| [Imp] maximum permanent current | 400 V : 1.3 x I1 |
| Colour code | (RAL 9001) |
| Height | 2000 mm |
| Width | 2150 mm |
| Depth | 600 mm |
| Product weight | 710 kg |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|--------------------|----------------|
| Compatibility code | VARSET_HARMONY |
|--------------------|----------------|

Environment

| | |
|---|---|
| Standards | EN 60439-1 IEC 60439-1 IEC 61921 |
| IP degree of protection | IP31 |
| Ambient air temperature for operation | -5...40 °C |
| Average ambient air temperature for operation | 25 °C (annual) 35 °C (over 24 hours) |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Product Life Status

END-OF-SALE NOTICE