

SIPLUS ET 200S EM 8 DO 24 V DC/ 0.5 -25...+70 °C based on
6ES7132-4BF50-0AA0



Supply voltage

Reverse voltage protection	Yes; when using the same correctly polarized load voltage as on the power module
----------------------------	----------------------------------------------------------------------------------

Load voltage L+

- | | |
|-------------------------------------------------------------------------------------------------------------|--------------------------------|
| <ul style="list-style-type: none"> • Rated value (DC) • Reverse polarity protection | 24 V; From power module
Yes |
|-------------------------------------------------------------------------------------------------------------|--------------------------------|

Input current

from load voltage L+ (without load), max.	5 mA
from backplane bus 3.3 V DC, max.	10 mA

Power loss

Power loss, typ.	1.5 W
------------------	-------

Address area

Address space per module	
<ul style="list-style-type: none"> • without packing 	1 byte

Digital outputs

Number of digital outputs	8
Short-circuit protection	Yes

• Response threshold, typ.	1.5 A
Limitation of inductive shutdown voltage to	Typ. 47 V
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	5 W
Load resistance range	
• lower limit	48 Ω
• upper limit	3 400 Ω
Output voltage	
• for signal "1", min.	Max. 1 V
Output current	
• for signal "1" rated value	0.5 A
• for signal "1" permissible range, min.	5 mA
• for signal "1" permissible range, max.	600 mA
• for signal "0" residual current, max.	5 μ A
Output delay with resistive load	
• "0" to "1", max.	300 μ s
• "1" to "0", max.	600 μ s
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes; per module
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	10 Hz
Total current of the outputs	
• Current per module, max.	4 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	Yes
Interrupts/diagnostics/status information	
Diagnostic functions	No
Diagnostics indication LED	
• Status indicator digital output (green)	Yes
Parameter	
Remark	3 byte
Potential separation	
Potential separation digital outputs	

- between the channels
- between the channels and backplane bus

No

Yes

Isolation

Isolation tested with 500 V DC

Ambient conditions

Ambient temperature during operation

- min. -25 °C; = Tmin
- max. 70 °C; = Tmax

Altitude during operation relating to sea level

- Installation altitude above sea level, max. 5 000 m
- Ambient air temperature-barometric pressure-altitude
Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)

Relative humidity

- With condensation, tested in accordance with IEC 60068-2-38, max. 100 %; RH incl. condensation/frost (no commissioning under condensation conditions)

Resistance

Use in stationary industrial systems

- to biologically active substances according to EN 60721-3-3 Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
- to chemically active substances according to EN 60721-3-3 Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
- to mechanically active substances according to EN 60721-3-3 Yes; Class 3S4 incl. sand, dust, *

Use on ships/at sea

- to biologically active substances according to EN 60721-3-6 Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
- to chemically active substances according to EN 60721-3-6 Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
- to mechanically active substances according to EN 60721-3-6 Yes; Class 6S3 incl. sand, dust; *

from supply voltage 1L+

- Note regarding classification of environmental conditions acc. to EN 60721 * The supplied plug covers must remain in place over the unused interfaces during operation!

Dimensions

Width 15 mm
Height 81 mm
Depth 52 mm

Weights

Weight, approx. 40 g

last modified:

05/18/2018