

SIPLUS ET 200S EM 2AI RTD -25...+70 °C with conformal coating based on 6ES7134-4JB51-0AB0



<b>Supply voltage</b>	
Load voltage L+	
• Rated value (DC)	24 V; From power module
• Reverse polarity protection	Yes
<b>Input current</b>	
from load voltage L+ (without load), max.	30 mA
from backplane bus 3.3 V DC, max.	10 mA
<b>Output voltage</b>	
Power supply to the transmitters	
• present	Yes
• short-circuit proof	Yes
<b>Power loss</b>	
Power loss, typ.	0.6 W
<b>Address area</b>	
Address space per module	
• Address space per module, max.	8 byte
<b>Analog inputs</b>	

Number of analog inputs	4; 2 for 3 or 4-wire connection
permissible input voltage for voltage input (destruction limit), max.	9 V
Constant measurement current for resistance-type transmitter, typ.	1.67 mA
Cycle time (all channels) max.	Number of active channels per module x basic conversion time
Technical unit for temperature measurement adjustable	No
<b>Input ranges</b>	
• Voltage	No
• Current	No
• Thermocouple	No
• Resistance thermometer	Yes
• Resistance	Yes
<b>Input ranges (rated values), resistance thermometer</b>	
• Ni 100	Yes; Standard/climate
• Input resistance (Ni 100)	2 000 k $\Omega$
• Pt 100	Yes; Standard/climate
• Input resistance (Pt 100)	2 000 k $\Omega$
<b>Input ranges (rated values), resistors</b>	
• 0 to 150 ohms	Yes
• Input resistance (0 to 150 ohms)	2 000 k $\Omega$
• 0 to 300 ohms	Yes
• Input resistance (0 to 300 ohms)	2 000 k $\Omega$
• 0 to 600 ohms	Yes
• Input resistance (0 to 600 ohms)	2 000 k $\Omega$
<b>Characteristic linearization</b>	
• parameterizable — for resistance thermometer	Yes; for Pt100, Ni100 Pt100 (standard, climatic range), Ni100 (standard, climatic range)
<b>Cable length</b>	
• shielded, max.	200 m
<b>Analog value generation for the inputs</b>	
Measurement principle	integrating
<b>Integration and conversion time/resolution per channel</b>	
• Resolution with overrange (bit including sign), max.	16 bit; 150 ohms: 14 bits; 300, 600 ohms: 15 bits, Pt100, Ni100: 16 bits
• Integration time, parameterizable	Yes
• Integration time (ms)	16,7 / 20 ms
• Interference voltage suppression for interference frequency f1 in Hz	50 / 60 Hz
• Conversion time (per channel)	66 / 80 ms; additional conversion time for diagnostic wire break test
<b>Smoothing of measured values</b>	

• parameterizable	Yes; In four stages by means of digital filtering
• Step: None	Yes; 1 x cycle time
• Step: low	Yes; 4 x cycle time
• Step: Medium	Yes; 32 x cycle time
• Step: High	Yes; 64 x cycle time

## Encoder

### Connection of signal encoders

• for resistance measurement with two-wire connection	Yes
• for resistance measurement with three-wire connection	Yes
• for resistance measurement with four-wire connection	Yes

## Errors/accuracies

Linearity error (relative to input range), (+/-)	0.01 %
Temperature error (relative to input range), (+/-)	0.005 %/K
Crosstalk between the inputs, min.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.05 %

### Operational error limit in overall temperature range

• Resistance thermometer, relative to input range, (+/-)	0.6 %
--	-------

### Basic error limit (operational limit at 25 °C)

• Resistance thermometer, relative to input range, (+/-)	0.4 %
--	-------

### Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$ , $f_1 =$ interference frequency

• Series mode interference (peak value of interference < rated value of input range), min.	70 dB
• Common mode interference (USS < 2.5 V), min.	90 dB

## Isochronous mode

Isochronous operation (application synchronized up to terminal)	No
---	----

## Interrupts/diagnostics/status information

### Diagnostic messages

• Wire-break	Yes
• Group error	Yes
• Overflow/underflow	Yes

### Diagnostics indication LED

• Group error SF (red)	Yes
------------------------	-----

## Parameter

Diagnostics wire break	Disable / enable
------------------------	------------------

Measurement type/range	deactivated/150 ohms/; 300 ohms/600 ohms/ Pt100 climatic/ Pt100 standard; Ni100 standard / Ni100 climatic, 2, 3 or 4-wire
Group diagnostics	Disable / enable
Overflow/underflow	Disable / enable

### Potential separation

Potential separation analog inputs	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes

### Permissible potential difference

between MANA and M internally (UISO)	75 V DC/60 V AC
--------------------------------------	-----------------

### Isolation

Isolation tested with	500 V DC
-----------------------	----------

### Standards, approvals, certificates

CE mark	Yes
---------	-----

### Ambient conditions

Ambient temperature during operation	
• min.	-25 °C; = Tmin
• max.	70 °C; = Tmax

### Altitude during operation relating to sea level

• Installation altitude above sea level, max.	5 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)

### Relative humidity

• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost permitted (no commissioning in bedewed state)
---	--

### Resistance

Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *

— to mechanically active substances  
according to EN 60721-3-6

Yes; Class 6S3 incl. sand, dust; \*

from supply voltage 1L+

— Note regarding classification of  
environmental conditions acc. to EN 60721

\* The supplied plug covers must remain in place over the unused  
interfaces during operation!

### Dimensions

Width	15 mm
Height	81 mm
Depth	52 mm

### Weights

Weight, approx. 40 g

**last modified:** 05/16/2018