

SIPLUS ET 200S TM-E15C26-A1 -40...+70 °C with conformal coating based on 6ES7193-4CA50-0AA0 5 units per packing unit . for electronic modules 15 mm width, Spring-type terminals, 2x6 terminal connections with terminal access to AUX1, AUX1 continuous

Standards, approvals, certificates

CE mark	Yes
---------	-----

Ambient conditions

Ambient temperature during operation

- | | |
|--------|----------------|
| • min. | -40 °C; = Tmin |
| • max. | 70 °C; = Tmax |

Altitude during operation relating to sea level

- | | |
|--|---|
| • Installation altitude above sea level, max. | 5 000 m |
| • Ambient air temperature-barometric pressure-altitude | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m) |

Relative humidity

- | | |
|---|--|
| • With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation/frost permitted (no commissioning in bedewed state) |
|---|--|

Resistance

Use in stationary industrial systems

- | | |
|---|--|
| — to biologically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request |
| — to chemically active substances according to EN 60721-3-3 | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust, * |

Use on ships/at sea

- | | |
|---|--|
| — to biologically active substances according to EN 60721-3-6 | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request |
| — to chemically active substances according to EN 60721-3-6 | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-6 | Yes; Class 6S3 incl. sand, dust; * |

from supply voltage 1L+

- | | |
|--|--|
| — Note regarding classification of environmental conditions acc. to EN 60721 | * The supplied plug covers must remain in place over the unused interfaces during operation! |
|--|--|

Dimensions

Width	15 mm
Height	157 mm
Depth	43 mm

Weights

Weight, approx.	70 g
-----------------	------

Scope of supply

Delivery quantity in pieces	5
-----------------------------	---

last modified: 05/16/2018