

SIPLUS ET 200S TM-E15N24-0 -40...+70 °C with conformal coating based on 6ES7193-4CB70-0AA0 5 units per packing unit . for electronic modules, 15 mm width, FastConnect terminal, 2x4 terminal connections without terminal access to AUX1, AUX1 continuous

### Standards, approvals, certificates

CE mark Yes

### Ambient conditions

#### Ambient temperature during operation

- min. -40 °C; = Tmin
- max. 70 °C; = Tmax

#### Altitude during operation relating to sea level

- Installation altitude above sea level, max. 5 000 m
- Ambient air temperature-barometric pressure-altitude Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)

#### Relative humidity

- With condensation, tested in accordance with IEC 60068-2-38, max. 100 %; RH incl. condensation/frost permitted (no commissioning in bedewed state)

### Resistance

#### Use in stationary industrial systems

- to biologically active substances according to EN 60721-3-3 Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
- to chemically active substances according to EN 60721-3-3 Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); \*
- to mechanically active substances according to EN 60721-3-3 Yes; Class 3S4 incl. sand, dust, \*

#### Use on ships/at sea

- to biologically active substances according to EN 60721-3-6 Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
- to chemically active substances according to EN 60721-3-6 Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); \*
- to mechanically active substances according to EN 60721-3-6 Yes; Class 6S3 incl. sand, dust; \*

#### from supply voltage 1L+

- Note regarding classification of environmental conditions acc. to EN 60721 \* The supplied plug covers must remain in place over the unused interfaces during operation!

### Dimensions

Width 15 mm

Height	162 mm
Depth	43 mm
<b>Weights</b>	
Weight, approx.	72 g
<b>Scope of supply</b>	
Delivery quantity in pieces	5
<b>last modified:</b>	05/16/2018