

SIPLUS S7-400 Y-coupler for medial exposure based on 6ES7197-11b00-0XA0

General information

Requirements for DP master system

- Length of parameter assignment telegram 244 byte

Supply voltage

Design of the power supply via bus module

permissible range, lower limit (DC) 20.4 V

permissible range, upper limit (DC) 28.8 V

Interfaces

PROFIBUS DP

Properties of the lower-level DP master system

- Transmission rate, max. 12 Mbit/s; 45.45 kbit/s to 12 Mbit/s
- Termination of lower-level DP master system Active terminating resistor (Bus Terminator)
- Use of OLM/OBT Yes
- Use of RS 485 repeaters, max. 9
- Number of DP slaves, max. 31; 64 when using RS 485 repeaters or OLM/OBT

Protocols

PROFIBUS DP Yes

Interrupts/diagnostics/status information

Status indicator No

Alarms No

Diagnostic functions Yes

Potential separation

to lower-level DP master system Yes

Ambient conditions

Ambient temperature during operation

- min. 0 °C; = Tmin
- max. 60 °C; = Tmax

Ambient temperature during storage/transportation

- min. -40 °C
- max. 70 °C

Altitude during operation relating to sea level

- Installation altitude above sea level, max. 5 000 m

<ul style="list-style-type: none"> • Ambient air temperature-barometric pressure-altitude 	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
<ul style="list-style-type: none"> • With condensation, tested in accordance with IEC 60068-2-38, max. 	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
from supply voltage 1L+	
— Note regarding classification of environmental conditions acc. to EN 60721	* The supplied plug covers must remain in place over the unused interfaces during operation!
Dimensions	
Width	40 mm
Height	125 mm
Depth	130 mm
Weights	
Weight, approx.	200 g
last modified:	05/16/2018