

SIPLUS S7-300 SM 326F DO8 according to EN 50155 T1 Cat 1 CI A/ B with conformal coating Based on 6ES7326-2BF41-0AB0 . Digital output F-DO 8x 24 V DC/2A PM fail-safe digital output Sinking-sourcing up to Category 4 (EN 954-1), SIL 3 (IEC 61508)

Supply voltage

Rated value (DC)	24 V; 1L+
Reverse polarity protection	Yes
Load voltage L+	
• Rated value (DC)	24 V; 2L+, 3L+
• Reverse polarity protection	No

Input current

from supply voltage 1L+, max.	75 mA
from load voltage 2L+ (without load), max.	100 mA
from load voltage 3L+ (without load), max.	100 mA
from backplane bus 5 V DC, max.	100 mA

Power loss

Power loss, typ.	12 W
------------------	------

Digital outputs

Number of digital outputs	8
Short-circuit protection	Yes
Limitation of inductive shutdown voltage to	L+ (-33 V)

Switching capacity of the outputs

• on lamp load, max.	5 W
----------------------	-----

Output voltage

• for signal "1", min.	L+ (-1.0 V)
------------------------	-------------

Output current

• for signal "1" rated value	2 A
• for signal "1" permissible range for 0 to 40 °C, min.	7 mA
• for signal "1" permissible range for 0 to 40 °C, max.	2 A; with horizontal installation, 1 A with vertical installation
• for signal "1" permissible range for 40 to 60 °C, min.	7 mA
• for signal "1" permissible range for 40 to 60 °C, max.	1 A; for horizontal installation
• for signal "0" residual current, max.	0.5 mA

Switching frequency

• with resistive load, max.	30 Hz
• with inductive load, max.	2 Hz
• on lamp load, max.	10 Hz
Total current of the outputs (per group)	
horizontal installation	
— up to 40 °C, max.	7.5 A
— up to 60 °C, max.	4 A
vertical installation	
— up to 40 °C, max.	5 A
Cable length	
• shielded, max.	200 m; 200 m for SIL3, AK 6, Cat 4
• unshielded, max.	200 m
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	Yes; Parameterizable
Diagnostic messages	
• Diagnostic information readable	Yes
Diagnostics indication LED	
• Fail-safe operation	Yes
• Group error SF (red)	Yes
Potential separation	
Potential separation digital outputs	
• between the channels	Yes
• between the channels, in groups of	4
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	Yes
Isolation	
Isolation tested with	500V AC for 1 min (internal voltage limiting to ±120V)
Standards, approvals, certificates	
CE mark	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
Railway application	
• EN 50155	Yes; Sections 4, 5 and 12; no further agreements apply; T1, Category 1, Class A/B, EN 50155:2007
Highest safety class achievable in safety mode	
• acc. to EN 954	Cat. 4
• SIL acc. to IEC 61508	SIL 3

Ambient conditions	
Ambient temperature during operation	
• min.	-25 °C; = Tmin
• max.	60 °C; = Tmax; the rated temperature range of -25 ... +55 °C (T1) applies for the use on railway vehicles according to EN50155
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on land craft, rail vehicles and special-purpose vehicles	
— to biologically active substances according to EN 60721-3-5	Yes; Class 5B2 mold, fungus and dry rot spores (with the exception of fauna); Class 5B3 on request
— to chemically active substances according to EN 60721-3-5	Yes; Class 5C3 (RH < 75 %) incl. salt spray acc. to EN 50155 (ST2); *
— to mechanically active substances according to EN 60721-3-5	Yes; Class 5S3 incl. sand, dust; *
from supply voltage 1L+	
— Note regarding classification of environmental conditions acc. to EN 60721	* The supplied plug covers must remain in place over the unused interfaces during operation!
Connection method	
required front connector	40-pin
Dimensions	
Width	80 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	465 g
last modified:	05/18/2018