

SIPLUS PS PSU100S 24 V/10 A
 SIPLUS PSU100S 24 V/10 A FOR MEDIAL STRESS BASED ON
 6EP1334-2BA20 . STABILIZED POWER SUPPLY INPUT: OUTPUT:
 24 V/10 A DC



Figure similar

Input	
Input	1-phase AC
Supply voltage	
<ul style="list-style-type: none"> • 1 at AC Rated value • 2 at AC Rated value • Note 	120 V 230 V Automatic range selection
Input voltage	
<ul style="list-style-type: none"> • 1 at AC • 2 at AC 	85 ... 132 V 170 ... 264 V
Wide-range input	No
Overvoltage resistance	$2.3 \times V_{in}$ rated, 1.3 ms
Mains buffering at I _{out} rated, min.	20 ms; at $V_{in} = 93/187$ V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
Input current	
<ul style="list-style-type: none"> • at rated input voltage 120 V 	4.49 A

• at rated input voltage 230 V	1.91 A
Switch-on current limiting (+25 °C), max.	60 A
I ² t, max.	5.6 A ² ·s
Built-in incoming fuse	T 6.3 A/250 V (not accessible)
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 10 A characteristic C

Output	
Output	Controlled, isolated DC voltage
Rated voltage V _{out} DC	24 V
Total tolerance, static ±	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	1 %
Residual ripple peak-peak, max.	150 mV
Residual ripple peak-peak, typ.	20 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	240 mV
Spikes peak-peak, typ. (bandwidth: 20 MHz)	160 mV
Adjustment range	22.8 ... 28 V
Product function Output voltage adjustable	Yes
Output voltage setting	via potentiometer
Status display	Green LED for 24 V OK
Signaling	Relay contact (NO contact, rating 60 V DC/ 0.3 A) for "24 V OK"
On/off behavior	Overshoot of V _{out} < 3 %
Startup delay, max.	0.3 s
Voltage rise, typ.	20 ms
Rated current value I _{out} rated	10 A
Current range	0 ... 12 A
• Note	12 A up to +45°C; +60 ... +70 °C: Derating 3%/K
Supplied active power typical	288 W
Short-term overload current	
• on short-circuiting during the start-up typical	32 A
• at short-circuit during operation typical	32 A
Duration of overloading capability for excess current	
• on short-circuiting during the start-up	1 000 ms
• at short-circuit during operation	1 000 ms
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2

Efficiency	
Efficiency at V _{out} rated, I _{out} rated, approx.	90 %
Power loss at V _{out} rated, I _{out} rated, approx.	25 W

Closed-loop control

Dynamic mains compensation (V_{in} rated $\pm 15\%$), max.	0.3 %
Dynamic load smoothing (I_{out} : 10/90/10 %), $U_{out} \pm$ typ.	3 %
Load step setting time 10 to 90%, typ.	1 ms
Load step setting time 90 to 10%, typ.	1 ms

Protection and monitoring

Output overvoltage protection	protection against overvoltage in case of internal fault $V_{out} < 33\text{ V}$
Current limitation	12 ... 14.6 A
Property of the output Short-circuit proof	Yes
Short-circuit protection	Constant current characteristic
Enduring short circuit current RMS value <ul style="list-style-type: none"> • typical 	14.6 A
Overcurrent overload capability in normal operation	overload capability 150 % I_{out} rated up to 5 s/min
Overload/short-circuit indicator	-

Safety

Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage U_{out} acc. to EN 60950-1 and EN 50178
Protection class	Class I
Leakage current <ul style="list-style-type: none"> • maximum • typical 	3.5 mA 0.8 mA
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
Explosion protection	IECEx Ex nA nC IIC T4 Gc; ATEX (EX) II 3G Ex nA nC IIC T4 Gc; cULus Class I Div. 2 (ANSI/ISA-12.12.01-2007, CSA C22.2 No. 213-M1987) Group ABCD, T4; cCSAus (CSA C22.2 No. 213, ANSI/ISA-12.12.01) Class I, Div. 2, Group ABCD, T4
FM approval	-
CB approval	Yes
Marine approval	BV, DNV GL
Degree of protection (EN 60529)	IP20

EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

Operating data

Ambient temperature <ul style="list-style-type: none"> • during operation — Note 	-25 ... +70 °C with natural convection
--	---

<ul style="list-style-type: none"> • during transport • during storage 	-40 ... +85 °C -40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K8H
Relative humidity with condensation maximum	100 %; Relative humidity, incl. condensation/frost permitted (no commissioning under condensation conditions)
Resistance to biologically active substances conformity acc. to EN 60721-3-3	Yes; Compliant with EN 60721-3-3, Class 3B2 mold and fungal spores (except fauna); the supplied plug covers must remain in place on the unused interfaces during operation.
Resistance to chemically active substances conformity acc. to EN 60721-3-3	Yes; Compliant with EN 60721-3-3, Class 3C4 incl. salt spray in accordance with EN 60068-2-52 (severity 3); the supplied plug covers must remain in place on the unused interfaces during operation.
Resistance to mechanically active substances conformity acc. to EN 60721-3-3	Yes; Conformity with EN 60721-3-3, Class 3S4 incl. Sand, dust. The supplied connector covers must remain on the unused interfaces during operation!

Mechanics

Connection technology	screw-type terminals
Connections	
<ul style="list-style-type: none"> • Supply input • Output • Auxiliary 	L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm ² single-core/finely stranded +, -: 2 screw terminals each for 0.5 ... 2.5 mm ² Alarm signals: 2 screw terminals for 0.5 ... 2.5 mm ²
Width of the enclosure	70 mm
Height of the enclosure	125 mm
Depth of the enclosure	120 mm
Required spacing	
<ul style="list-style-type: none"> • top • bottom • left • right 	50 mm 50 mm 0 mm 0 mm
Weight, approx.	0.8 kg
Product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15
Electrical accessories	Buffer module
MTBF at 40 °C	1 614 510 h
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)