

SIPLUS S7-400 rack UR2-H -25...+70 °C with conformal coating based on 6ES7400-2JA10-0AA0 . central and distributed with 2x 9 slots



Figure similar

| General information                               |                |
|---|----------------|
| Product type designation                          | UR2-H          |
| Hardware configuration                            |                |
| Rack  |                |
| • Communication bus                               | Yes            |
| • P bus   | Yes            |
| Slots   |                |
| • Number of single-width slots, max.              | 18             |
| Ambient conditions                                |                |
| Ambient temperature during operation              |                |
| • min.  | -25 °C; = Tmin |
| • max.  | 70 °C; = Tmax  |
| Ambient temperature during storage/transportation |                |
| • min.  | -40 °C         |
| • max.  | 70 °C          |
| Altitude during operation relating to sea level   |                |

|   |   |
|---|---|
| <ul style="list-style-type: none"> <li>• Installation altitude above sea level, max.</li> <li>• Ambient air temperature-barometric pressure-altitude</li> </ul> | <p>5 000 m</p> <p>Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)</p> |
| <b>Relative humidity</b>  |   |
| <ul style="list-style-type: none"> <li>• With condensation, tested in accordance with IEC 60068-2-38, max.</li> </ul>   | 100 %; RH incl. condensation/frost (no commissioning under condensation conditions)   |
| <b>Resistance</b>   |   |
| <b>Use in stationary industrial systems</b>   |   |
| — to biologically active substances according to EN 60721-3-3   | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request  |
| — to chemically active substances according to EN 60721-3-3   | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *  |
| — to mechanically active substances according to EN 60721-3-3   | Yes; Class 3S4 incl. sand, dust, *  |
| <b>Use on ships/at sea</b>  |   |
| — to biologically active substances according to EN 60721-3-6   | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request   |
| — to chemically active substances according to EN 60721-3-6   | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *  |
| — to mechanically active substances according to EN 60721-3-6   | Yes; Class 6S3 incl. sand, dust; *  |
| <b>from supply voltage 1L+</b>  |   |
| — Note regarding classification of environmental conditions acc. to EN 60721  | * The supplied plug covers must remain in place over the unused interfaces during operation!  |
| <b>Dimensions</b>   |   |
| Width   | 482.5 mm  |
| Height  | 290 mm  |
| Depth   | 27.5 mm   |
| <b>Weights</b>  |   |
| Weight, approx.   | 3 000 g   |
| <b>last modified:</b>   | 05/16/2018  |