

SIPLUS S7-400 CPU 417-5H -25...+70 °C with conformal coating based on 6ES7417-5HT06-0AB0 . Central processing unit for S7-400H, and S7-400F/FH 5 interfaces: 1x MPI/DP, 1x DP, 1x PN and 2 for SYNC modules, 32 MB memory (16 MB data/16 MB program)



Figure similar

| General information | |
|---|--|
| Product type designation | CPU 417-5H PN/DP |
| HW functional status | 1 |
| Firmware version | V6.0 |
| Engineering with | |
| <ul style="list-style-type: none"> Programming package | As of STEP 7 V5.5 SP2 with HF1 |
| CiR – Configuration in RUN | |
| CiR synchronization time, basic load | 60 ms |
| CiR synchronization time, time per I/O byte | 0 µs |
| Supply voltage | |
| Rated value (DC) | |
| <ul style="list-style-type: none"> 24 V DC | No; Power supply via system power supply |
| Input current | |
| from backplane bus 5 V DC, typ. | 1.6 A |
| from backplane bus 5 V DC, max. | 1.9 A |
| from backplane bus 24 V DC, max. | 150 mA; 150 mA per DP interface |

| | |
|--|--|
| from interface 5 V DC, max. | 90 mA; At each DP interface |
| Power loss | |
| Power loss, typ. | 7.5 W |
| Memory | |
| Type of memory | RAM |
| Work memory | |
| <ul style="list-style-type: none"> • integrated • integrated (for program) • integrated (for data) • expandable | <ul style="list-style-type: none"> 32 Mbyte 16 Mbyte 16 Mbyte No |
| Load memory | |
| <ul style="list-style-type: none"> • expandable FEPRM • expandable FEPRM, max. • integrated RAM, max. • expandable RAM • expandable RAM, max. | <ul style="list-style-type: none"> Yes; with Memory Card (FLASH) 64 Mbyte 1 Mbyte Yes 64 Mbyte |
| Backup | |
| <ul style="list-style-type: none"> • present • with battery • without battery | <ul style="list-style-type: none"> Yes Yes; all data No |
| Battery | |
| Backup battery | |
| <ul style="list-style-type: none"> • Backup current, typ. • Backup current, max. • Backup time, max. • Feeding of external backup voltage to CPU | <ul style="list-style-type: none"> 180 μA; Valid up to 40°C 1 000 μA Dealt with in the module data manual with the secondary conditions and the factors of influence 5 V DC to 15 V DC |
| CPU processing times | |
| for bit operations, typ. | 7.5 ns |
| for word operations, typ. | 7.5 ns |
| for fixed point arithmetic, typ. | 7.5 ns |
| for floating point arithmetic, typ. | 15 ns |
| CPU-blocks | |
| DB | |
| <ul style="list-style-type: none"> • Number, max. • Size, max. | <ul style="list-style-type: none"> 16 000; Number range: 1 to 16000 64 kbyte |
| FB | |
| <ul style="list-style-type: none"> • Number, max. • Size, max. | <ul style="list-style-type: none"> 8 000; Number range: 0 to 7999 64 kbyte |
| FC | |

| | |
|---|--|
| • Number, max. | 8 000; Number range: 0 to 7999 |
| • Size, max. | 64 kbyte |
| OB | |
| • Number, max. | see instruction list |
| • Size, max. | 64 kbyte |
| • Number of free cycle OBs | 1; OB 1 |
| • Number of time alarm OBs | 8; OB 10-17 |
| • Number of delay alarm OBs | 4; OB 20-23 |
| • Number of cyclic interrupt OBs | 9; OB 30-38 |
| • Number of process alarm OBs | 8; OB 40-47 |
| • Number of DPV1 alarm OBs | 3; OB 55-57 |
| • Number of startup OBs | 2; OB 100, 102 |
| • Number of asynchronous error OBs | 9; OB 80-88 |
| • Number of synchronous error OBs | 2; OB 121, 122 |
| Nesting depth | |
| • per priority class | 24 |
| • additional within an error OB | 2 |
| Counters, timers and their retentivity | |
| S7 counter | |
| • Number | 2 048 |
| Retentivity | |
| — adjustable | Yes |
| — lower limit | 0 |
| — upper limit | 2 047 |
| — preset | Z 0 to Z 7 |
| Counting range | |
| — lower limit | 0 |
| — upper limit | 999 |
| IEC counter | |
| • Number | Unlimited (limited only by RAM capacity) |
| S7 times | |
| • Number | 2 048 |
| Retentivity | |
| — adjustable | Yes |
| — lower limit | 0 |
| — upper limit | 2 047 |
| — preset | No times retentive |
| Time range | |
| — lower limit | 10 ms |
| — upper limit | 9 990 s |
| IEC timer | |

| | |
|-----------|--|
| • present | Yes |
| • Type | SFB |
| • Number | Unlimited (limited only by RAM capacity) |

Data areas and their retentivity

| | |
|------------------------------|---|
| retentive data area in total | Total working and load memory (with backup battery) |
| Flag | |
| • Number, max. | 16 384 byte |
| • Retentivity available | Yes |
| • Retentivity preset | MB 0 to MB 15 |
| • Number of clock memories | 8; in 1 memory byte |
| Local data | |
| • adjustable, max. | 64 kbyte |
| • preset | 32 kbyte |

Address area

| | |
|--|------------|
| I/O address area | |
| • Inputs | 16 kbyte |
| • Outputs | 16 kbyte |
| of which distributed | |
| — MPI/DP interface, inputs | 2 kbyte |
| — MPI/DP interface, outputs | 2 kbyte |
| — DP interface, inputs | 8 kbyte |
| — DP interface, outputs | 8 kbyte |
| — PROFINET interface, inputs | 8 kbyte |
| — PROFINET interface, outputs | 8 kbyte |
| Process image | |
| • Inputs, adjustable | 8 kbyte |
| • Outputs, adjustable | 8 kbyte |
| • Inputs, default | 1 024 byte |
| • Outputs, default | 1 024 byte |
| • consistent data, max. | 244 byte |
| • Access to consistent data in process image | Yes |
| Subprocess images | |
| • Number of subprocess images, max. | 15 |
| Digital channels | |
| • Inputs | 131 072 |
| — of which central | 131 072 |
| • Outputs | 131 072 |
| — of which central | 131 072 |
| Analog channels | |
| • Inputs | 8 192 |
| — of which central | 8 192 |

- Outputs 8 192
- of which central 8 192

Hardware configuration

| | |
|---|---|
| Number of expansion units, max. | 21 |
| connectable OPs | 119 |
| Multicomputing | No |
| Interface modules | |
| • Number of connectable IMs (total), max. | 6 |
| • Number of connectable IM 460s, max. | 6 |
| • Number of connectable IM 463s, max. | 4; Single mode only |
| Number of DP masters | |
| • integrated | 2 |
| • via CP | 10; CP 443-5 Extended |
| • Mixed mode IM + CP permitted | No |
| • via interface module | 0 |
| Number of IO Controllers | |
| • integrated | 1 |
| • via CP | 0 |
| Number of operable FMs and CPs (recommended) | |
| • FM | See manual Automation System S7-400H fault-tolerant systems. Limited by number of slots and number of connections |
| • CP, PtP | See manual Automation System S7-400H fault-tolerant systems. Limited by number of slots and number of connections |
| • PROFIBUS and Ethernet CPs | 14; Of which max. 10 CP as DP master |
| Slots | |
| • required slots | 2 |
| Time of day | |
| Clock | |
| • Hardware clock (real-time) | Yes |
| • retentive and synchronizable | Yes |
| • Resolution | 1 ms |
| • Deviation per day (buffered), max. | 1.7 s; Power off |
| • Deviation per day (unbuffered), max. | 8.6 s; Power on |
| Operating hours counter | |
| • Number | 16 |
| • Number/Number range | 0 to 15 |
| • Range of values | SFCs 2, 3 and 4: 0 to 32767 hours SFC 101: 0 to 2 ³¹ - 1 hours |
| • retentive | Yes |
| Clock synchronization | |
| • supported | Yes |
| • to MPI, master | Yes |

| | |
|-----------------------|----------------|
| • to MPI, slave | Yes |
| • to DP, master | Yes |
| • to DP, slave | Yes |
| • in AS, master | Yes |
| • in AS, slave | Yes |
| • on Ethernet via NTP | Yes; As client |

| | |
|---|----------------|
| Time difference in system when synchronizing via | |
| • Ethernet, max. | 10 ms; Via NTP |
| • MPI, max. | 200 ms |

Interfaces

| | |
|-----------------------------|--------------------------|
| Number of RS 485 interfaces | 2 |
| Number of other interfaces | 2; Fiber-optic interface |

1. Interface

| | |
|---|-------------------------|
| Interface type | Integrated |
| Physics | RS 485 / PROFIBUS + MPI |
| Isolated | Yes |
| Power supply to interface (15 to 30 V DC), max. | 150 mA |
| Number of connection resources | MPI: 44, DP: 32 |

| | |
|----------------------|-----|
| Functionality | |
| • MPI | Yes |
| • PROFIBUS DP master | Yes |
| • PROFIBUS DP slave | No |

| | |
|---------------------------|---|
| MPI | |
| • Number of connections | 44; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1 |
| • Transmission rate, max. | 12 Mbit/s |

| | |
|-------------------------------|-----|
| Services | |
| — PG/OP communication | Yes |
| — Routing | Yes |
| — Global data communication | No |
| — S7 basic communication | No |
| — S7 communication | Yes |
| — S7 communication, as client | Yes |
| — S7 communication, as server | Yes |

| | |
|-------------------------------|---|
| DP master | |
| • Number of connections, max. | 32; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1 |
| • Transmission rate, max. | 12 Mbit/s |
| • Number of DP slaves, max. | 32 |

| | |
|-----------------------|-----|
| Services | |
| — PG/OP communication | Yes |

| | |
|---|-------------------------------------|
| — Routing | Yes |
| — Global data communication | No |
| — S7 basic communication | No |
| — S7 communication | Yes |
| — S7 communication, as client | Yes |
| — S7 communication, as server | Yes |
| — Equidistance | No |
| — Isochronous mode | No |
| — SYNC/FREEZE | No |
| — Activation/deactivation of DP slaves | No |
| — Direct data exchange (slave-to-slave communication) | No |
| — DPV1 | Yes |
| Address area | |
| — Inputs, max. | 2 kbyte |
| — Outputs, max. | 2 kbyte |
| User data per DP slave | |
| — User data per DP slave, max. | 244 byte |
| — Inputs, max. | 244 byte |
| — Outputs, max. | 244 byte |
| — Slots, max. | 244 |
| — per slot, max. | 128 byte |
| DP slave | |
| • Number of connections | No configuration of CPU as DP slave |
| 2. Interface | |
| Interface type | PROFINET |
| Physics | Ethernet RJ45 |
| Isolated | Yes |
| automatic detection of transmission rate | Yes; Autosensing |
| Autonegotiation | Yes |
| Autocrossing | Yes |
| Change of IP address at runtime, supported | No |
| Number of connection resources | 120 |
| Interface types | |
| • Number of ports | 2 |
| • integrated switch | Yes |
| Media redundancy | |
| • supported | Yes |
| • Switchover time on line break, typ. | 200 ms |
| • Number of stations in the ring, max. | 50 |
| Functionality | |
| • PROFINET IO Controller | Yes |

| | |
|---|---|
| • PROFINET IO Device | No |
| • PROFINET CBA | No |
| • PROFIBUS DP master | No |
| • PROFIBUS DP slave | No |
| • Open IE communication | Yes |
| • Web server | No |
| • Point-to-point connection | No |
| PROFINET IO Controller | |
| • Transmission rate, max. | 100 Mbit/s |
| Services | |
| — PG/OP communication | Yes |
| — S7 routing | Yes |
| — S7 communication | Yes |
| — Isochronous mode | No |
| — Open IE communication | Yes |
| — Shared device | Yes; Single mode only |
| — Prioritized startup | No |
| — Number of connectable IO Devices, max. | 256; In redundant mode via both interfaces |
| — Number of connectable IO Devices for RT, max. | 256 |
| — of which in line, max. | 256 |
| — Activation/deactivation of IO Devices | No |
| — IO Devices changing during operation (partner ports), supported | No |
| — Device replacement without swap medium | Yes |
| — Send cycles | 250 µs, 500 µs, 1 ms, 2 ms, 4 ms |
| — Updating time | 250 µs to 512 ms, minimum value depends on the number of configured user data and the configured single or redundant mode |
| Address area | |
| — Inputs, max. | 8 kbyte |
| — Outputs, max. | 8 kbyte |
| — User data consistency, max. | 1 024 byte |
| Open IE communication | |
| • Number of connections, max. | 46 |
| • Local port numbers used at the system end | 0, 20, 21, 25, 102, 135, 161, 34962, 34963, 34964, 65532, 65533, 65534, 65535 |
| • Keep-alive function, supported | Yes |
| 3. Interface | |
| Interface type | Integrated |
| Physics | RS 485 / PROFIBUS |
| Power supply to interface (15 to 30 V DC), max. | 150 mA |
| Number of connection resources | 32 |

| Functionality | |
|---|--|
| • PROFIBUS DP master | Yes |
| • PROFIBUS DP slave | No |
| DP master | |
| • Number of connections, max. | 32 |
| • Number of DP slaves, max. | 125 |
| Services | |
| — PG/OP communication | Yes |
| — Routing | Yes |
| — Global data communication | No |
| — S7 basic communication | No |
| — S7 communication | Yes |
| — S7 communication, as client | Yes |
| — S7 communication, as server | Yes |
| — Equidistance | No |
| — Isochronous mode | No |
| — SYNC/FREEZE | No |
| — Activation/deactivation of DP slaves | No |
| — Direct data exchange (slave-to-slave communication) | No |
| — DPV0 | Yes |
| — DPV1 | Yes |
| Address area | |
| — Inputs, max. | 8 kbyte |
| — Outputs, max. | 8 kbyte |
| User data per DP slave | |
| — User data per DP slave, max. | 244 byte |
| — Inputs, max. | 244 byte |
| — Outputs, max. | 244 byte |
| — Slots, max. | 244 |
| — per slot, max. | 128 byte |
| 4. Interface | |
| Interface type | Pluggable synchronization submodule (FO) |
| Plug-in interface modules | Synchronization modules 6AG1960-1AA06-7XA0 or 6AG1960-1AB06-7XA0 |
| 5. Interface | |
| Interface type | Pluggable synchronization submodule (FO) |
| Plug-in interface modules | Synchronization modules 6AG1960-1AA06-7XA0 or 6AG1960-1AB06-7XA0 |
| Protocols | |
| SIMATIC communication | |

| | |
|---|---|
| • S7 routing | Yes |
| Open IE communication | |
| • TCP/IP | Yes; via integrated PROFINET interface and loadable FBs |
| — Data length, max. | 32 kbyte |
| — several passive connections per port, supported | Yes |
| • ISO-on-TCP (RFC1006) | Yes; Via integrated PROFINET interface or CP 443-1 and loadable FBs |
| — Data length, max. | 32 kbyte; 1452 bytes via CP 443-1 Adv. |
| • UDP | Yes; via integrated PROFINET interface and loadable FBs |
| — Number of connections, max. | 118 |
| — Data length, max. | 1 472 byte |
| Isochronous mode | |
| Isochronous operation (application synchronized up to terminal) | No |
| Equidistance | No |
| Communication functions | |
| PG/OP communication | Yes |
| • Number of connectable OPs without message processing | 119 |
| • Number of connectable OPs with message processing | 119; When using Alarm_S/SQ and Alarm_D/DQ |
| Data record routing | Yes |
| Global data communication | |
| • supported | No |
| S7 basic communication | |
| • supported | No |
| S7 communication | |
| • supported | Yes |
| • as server | Yes |
| • as client | Yes |
| • User data per job, max. | 64 kbyte |
| • User data per job (of which consistent), max. | 462 byte; 1 variable |
| S5 compatible communication | |
| • supported | Yes; (via CP max. 10 and FC AG_SEND and FC AG_RECV) |
| • User data per job, max. | 8 kbyte |
| • User data per job (of which consistent), max. | 240 byte |
| • Number of simultaneous AG-SEND/AG-RECV orders per CPU, max. | 64/64 |
| Standard communication (FMS) | |
| • supported | Yes; Via CP and loadable FB |
| Web server | |

| | |
|---|-----|
| • supported | No |
| Number of connections | |
| • overall | 120 |
| • usable for PG communication | |
| — reserved for PG communication | 1 |
| — adjustable for PG communication, max. | 0 |
| • usable for OP communication | |
| — reserved for OP communication | 1 |
| — adjustable for OP communication, max. | 0 |
| • usable for S7 basic communication | |
| — reserved for S7 basic communication | 0 |
| — adjustable for S7 basic communication, max. | 0 |
| • usable for S7 communication | |
| — reserved for S7 communication | 0 |
| — adjustable for S7 communication, max. | 0 |
| • usable for routing | |
| — reserved for routing | 0 |
| — adjustable for routing, max. | 0 |

| | |
|---|--|
| S7 message functions | |
| Number of login stations for message functions, max. | 119; Max. 119 with Alarm_S/SQ and Alarm_D/DQ (OPs); max. 16 with Alarm_8, Alarm_8P, Notify and Notify_8 (e.g. WinCC) |
| Symbol-related messages | No |
| SCAN procedure | No |
| Program alarms | Yes |
| Process diagnostic messages | Yes |
| simultaneously active Alarm-S blocks, max. | 1 000; Simultaneously active alarm_S/SQ blocks or alarm_D/DQ blocks |
| Alarm 8-blocks | Yes |
| • Number of instances for alarm 8 and S7 communication blocks, max. | 10 000 |
| • preset, max. | 1 200 |
| Process control messages | Yes |
| Number of archives that can log on simultaneously (SFB 37 AR_SEND) | 64 |

| | |
|-------------------------------------|-------------------------------|
| Test commissioning functions | |
| Status block | Yes |
| Single step | Yes |
| Number of breakpoints | 16 |
| Status/control | |
| • Status/control variable | Yes; Up to 16 variable tables |

| | |
|---|--|
| • Variables | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters |
| • Number of variables, max. | 70 |
| Forcing | |
| • Forcing | Yes |
| • Forcing, variables | Inputs/outputs, bit memories, distributed I/Os |
| • Number of variables, max. | 512 |
| Diagnostic buffer | |
| • present | Yes |
| • Number of entries, max. | 3 200 |
| — adjustable | Yes |
| — preset | 120 |
| Service data | |
| • can be read out | Yes |
| EMC | |
| Emission of radio interference acc. to EN 55 011 | |
| • Limit class A, for use in industrial areas | Yes |
| • Limit class B, for use in residential areas | No |
| Standards, approvals, certificates | |
| CE mark | Yes |
| Ambient conditions | |
| Ambient temperature during operation | |
| • min. | -25 °C; = Tmin |
| • max. | 70 °C; = Tmax; @ 60°C for UL/ATEX/FM and safety-related application |
| Ambient temperature during storage/transportation | |
| • min. | -40 °C |
| • max. | 70 °C |
| Altitude during operation relating to sea level | |
| • Installation altitude above sea level, max. | 5 000 m |
| • Ambient air temperature-barometric pressure-altitude | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m); with "F-System" applications max. +2 000 m above sea level permissible |
| Relative humidity | |
| • With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation/frost (no commissioning under condensation conditions) |
| Resistance | |
| Use in stationary industrial systems | |
| — to biologically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request |

| | |
|--|--|
| — to chemically active substances according to EN 60721-3-3 | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust, * |
| Use on ships/at sea | |
| — to biologically active substances according to EN 60721-3-6 | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request |
| — to chemically active substances according to EN 60721-3-6 | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-6 | Yes; Class 6S3 incl. sand, dust; * |
| from supply voltage 1L+ | |
| — Note regarding classification of environmental conditions acc. to EN 60721 | * The supplied plug covers must remain in place over the unused interfaces during operation! |

Configuration

| | |
|--|----------------------|
| Configuration software | |
| • STEP 7 | Yes |
| Programming | |
| • Command set | see instruction list |
| • Nesting levels | 7 |
| • Access to consistent data in process image | Yes |
| • System functions (SFC) | see instruction list |
| • System function blocks (SFB) | see instruction list |
| Programming language | |
| — LAD | Yes |
| — FBD | Yes |
| — STL | Yes |
| — SCL | Yes |
| — CFC | Yes |
| — GRAPH | Yes |
| — HiGraph® | Yes |
| Number of simultaneously active SFCs | |
| — RD_REC | 8 |
| — WR_REC | 8 |
| — WR_PARM | 8 |
| — PARM_MOD | 1 |
| — WR_DPARM | 2 |
| — DPNRM_DG | 8 |
| — RDSYSST | 8 |
| — DP_TOPOL | 1 |
| Number of simultaneously active SFBs | |
| — RDREC | 8 |

— WRREC

8

Know-how protection

- User program protection/password protection
- Block encryption

Yes

Yes; With S7 block Privacy

Dimensions

Width

50 mm

Height

290 mm

Depth

219 mm

Weights

Weight, approx.

995 g

last modified:

05/18/2018