

SIPLUS S7-1500 DI 16x230V AC BA -40...+70 °C with conformal coating based on 6ES7521-1FH00-0AA0 . Digital input module DI 16x230 V AC, "16 channels in groups of 4;" "Input delay 20ms;" Input type 1 (IEC 61131)



Figure similar

General information	
Product type designation	DI 16x230VAC BA
Product function	
• I&M data	Yes; I&M0 to I&M3
Power	
Power available from the backplane bus	1 W
Power loss	
Power loss, typ.	4.9 W
Digital inputs	
Number of digital inputs	16; > +60 °C, number of simultaneously controllable inputs max. 8
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input voltage	
• Type of input voltage	AC
• Rated value (AC)	230 V; 120/230 V AC (47 Hz to 63 Hz)
• for signal "0"	0V AC to 40V AC

• for signal "1"	79V AC to 264V AC
Input current	
• for signal "1", typ.	11 mA; At 230 V AC/50 Hz and 6.5 mA at 120 V AC/50 Hz
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", max.	25 ms
— at "1" to "0", max.	25 ms
for interrupt inputs	
— parameterizable	No
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	2 mA
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	No
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	No
• Hardware interrupt	No
Diagnostic messages	
• Monitoring the supply voltage	No
• Wire-break	No
• Short-circuit	No
• Fuse blown	No
Diagnostics indication LED	
• RUN LED	Yes; Green LED
• ERROR LED	Yes; Red LED
• Monitoring of the supply voltage (PWR-LED)	No
• Channel status display	Yes; Green LED
• for channel diagnostics	No
• for module diagnostics	Yes; Red LED
Potential separation	
Potential separation channels	
• between the channels	No

<ul style="list-style-type: none"> • between the channels, in groups of • between the channels and backplane bus 	4 Yes
Permissible potential difference	
between different circuits	250 V AC between the channels and the backplane bus; 500 V AC between the channels
Isolation	
Isolation tested with	2500 V DC
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • horizontal installation, min. • horizontal installation, max. • vertical installation, min. • vertical installation, max. 	-40 °C; = Tmin 70 °C; = Tmax; > +60 °C number of simultaneously controllable inputs max. 8 -40 °C; = Tmin 40 °C; = Tmax
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> • Installation altitude above sea level, max. • Ambient air temperature-barometric pressure-altitude 	2 000 m Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
Relative humidity	
<ul style="list-style-type: none"> • With condensation, tested in accordance with IEC 60068-2-38, max. 	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust, *
from supply voltage 1L+	
— Note regarding classification of environmental conditions acc. to EN 60721	* The supplied plug covers must remain in place over the unused interfaces during operation!

Decentralized operation

Fast Startup supported	Yes; 500 ms
------------------------	-------------

Dimensions

Width	35 mm
-------	-------

Height	147 mm
--------	--------

Depth	129 mm
-------	--------

Weights

Weight, approx.	200 g
-----------------	-------

last modified:	05/16/2018
-----------------------	------------