

SIPLUS S7-1500 front flap V2 CPU 70 mm -25...+60 °C Startup -20 °C with conformal coating based on 6ES7591-1BA01-0AA0 .  
 SIMATIC S7-1500, Spare part Display for CPU 1515 (F)-2 PN, CPU 1516 (F)-3 PN/DP, CPU 1517 (F)-3 PN/DP and CPU 1518 (F)-4 PN/DP



Figure similar

Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-20 °C; = Tmin
• horizontal installation, max.	60 °C; = Tmax
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes
Use in stationary industrial systems	

- to biologically active substances according to EN 60721-3-3
- to chemically active substances according to EN 60721-3-3
- to mechanically active substances according to EN 60721-3-3

Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request

Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); \*

Yes; Class 3S4 incl. sand, dust, \*

#### Use on ships/at sea

- to biologically active substances according to EN 60721-3-6
- to chemically active substances according to EN 60721-3-6
- to mechanically active substances according to EN 60721-3-6

Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request

Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); \*

Yes; Class 6S3 incl. sand, dust; \*

#### from supply voltage 1L+

- Note regarding classification of environmental conditions acc. to EN 60721

\* The supplied plug covers must remain in place over the unused interfaces during operation!

#### Other

Note:

At temperatures below 0 °C legibility may be restricted and representation of dynamic contents may be slower

**last modified:**

05/16/2018