

SIPLUS ET 200SP F-DQ 4 x 24 V DC/2 A PM RAIL -25 ... +55°C T1
with 70°C for 10 min with conformal coating Based on: 6ES7136-
6DB00-0CA0 . 15 mm overall width, up to PL E (ISO13849) up to SIL
3 (IEC 61508)

General information

Product type designation	F-DQ 4x24VDC HF
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3

Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes

Input current

Current consumption (rated value)	75 mA; without load
Current consumption, max.	21 mA; From the backplane bus

Output voltage

Rated value (DC)	24 V
------------------	------

Power

Power available from the backplane bus	70 mW
--	-------

Power loss

Power loss, typ.	4 W
------------------	-----

Address area

Address space per module	
<ul style="list-style-type: none"> Inputs 	5 byte
<ul style="list-style-type: none"> Outputs 	5 byte

Digital outputs

Number of digital outputs	4
Short-circuit protection	Yes
<ul style="list-style-type: none"> Response threshold, typ. 	> 3.3 A
Open-circuit detection	Yes
<ul style="list-style-type: none"> Response threshold, typ. 	8 mA
Overload protection	Yes
<ul style="list-style-type: none"> Response threshold, typ. 	2.9 A
Limitation of inductive shutdown voltage to	typ. 2*47V

Switching capacity of the outputs	
• with resistive load, max.	2 A
• on lamp load, max.	10 W
Load resistance range	
• lower limit	12 Ω
• upper limit	2 000 Ω
Output voltage	
• for signal "1", min.	24 V; L+ (-0.5 V)
Output current	
• for signal "1" rated value	2 A
• for signal "0" residual current, max.	0.5 mA
Switching frequency	
• with resistive load, max.	30 Hz; Symmetrical
• with inductive load, max.	0.1 Hz; according to IEC 60947-5-1, DC-13, symmetrical
• on lamp load, max.	10 Hz; Symmetrical
Total current of the outputs	
• Current per channel, max.	2 A; Note derating data in the manual
• Current per module, max.	6 A; Note derating data in the manual
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	500 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes, "Alarms/diagnostic messages" section in the manual
Substitute values connectable	No
Alarms	
• Diagnostic alarm	Yes
Diagnostics indication LED	
• RUN LED	Yes; Green LED
• ERROR LED	Yes; Red LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• Channel status display	Yes; Green LED
• for channel diagnostics	Yes; Red LED
• for module diagnostics	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
• between the channels	No
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	No
Permissible potential difference	
between different circuits	75 V DC/60 V AC

Isolation	
Isolation tested with	707 V DC (type test) and according to EN 50155 (routine test)
Standards, approvals, certificates	
Railway application	
<ul style="list-style-type: none"> • EN 50121-3-2 • EN 50121-4 • EN 50124-1 • EN 50125-1 • EN 50125-2 • EN 50125-3 • EN 50155 • EN 61373 • Fire protection acc. to EN 45545-2 	<p>Yes; EMC for rail vehicles</p> <p>Yes; EMC for signal and telecommunications systems</p> <p>Yes; Railway applications - overvoltage category OV2; pollution degree PD2; rated surge voltage UNi = 0.5 kV; UNm = 24 V DC</p> <p>Yes; Rail vehicles - see ambient conditions</p> <p>Yes; Stationary electrical equipment - see ambient conditions</p> <p>Yes; Signal and telecommunications systems - see ambient conditions; vibrations and shocks: Application point outside of tracks (1 m to 3 m away from track)</p> <p>Yes; Rail vehicles - temperature class T1, horizontal mounting position, salt spray Class ST2</p> <p>Yes; Rail vehicles - vibrations and shocks: Category 1 Class A/B</p> <p>Yes; Rail vehicles - verification on request</p>
Highest safety class achievable in safety mode	
<ul style="list-style-type: none"> • SIL in accordance with EN 50126, 50128, 50129 	SIL 2; a higher safety integrity level is possible if tested and approved for the specific application under consideration of all local regulations.
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • horizontal installation, min. • horizontal installation, max. 	<p>-25 °C; = Tmin</p> <p>60 °C; = Tmax; +70 °C for 10 min (T1 acc. to EN 50155)</p>
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> • Installation altitude above sea level, max. • Ambient air temperature-barometric pressure-altitude 	<p>2 000 m</p> <p>Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)</p>
Relative humidity	
<ul style="list-style-type: none"> • With condensation, tested in accordance with IEC 60068-2-38, max. 	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Coolants and lubricants	
<ul style="list-style-type: none"> — Resistant to commercially available coolants and lubricants 	Yes
Use in stationary industrial systems	
<ul style="list-style-type: none"> — to biologically active substances according to EN 60721-3-3 — to chemically active substances according to EN 60721-3-3 — to mechanically active substances according to EN 60721-3-3 	<p>Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request</p> <p>Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *</p> <p>Yes; Class 3S4 incl. sand, dust, *</p>

Use on land craft, rail vehicles and special-purpose vehicles

— to biologically active substances according to EN 60721-3-5

Yes; Class 5B2 mold, fungus and dry rot spores (with the exception of fauna); Class 5B3 on request

— to chemically active substances according to EN 60721-3-5

Yes; Class 5C3 (RH < 75 %) incl. salt spray acc. to EN 50155 (ST2); *

— to mechanically active substances according to EN 60721-3-5

Yes; Class 5S3 incl. sand, dust; *

from supply voltage 1L+

— Note regarding classification of environmental conditions acc. to EN 60721

* The supplied plug covers must remain in place over the unused interfaces during operation!

Dimensions

Width

15 mm

Weights

Weight, approx.

57 g

Other

Note:

For use in railway applications, also observe the product information "SIPLUS extreme RAIL" A5E37661960A Online Support article 109736776

last modified:

05/18/2018