

SIPLUS ET 200SP BA 2xRJ45 TX RAIL -40 ... +70 °C TX with 85 °C for 10 minutes with conformal coating Based on: 6ES7193-6AR00-0AA0 . Bus Adapter BA 2x RJ45, 2 RJ45 connectors for PROFINET



Figure similar

General information	
Product type designation	BA 2xRJ45
Interfaces	
Number of PROFINET interfaces	1
PROFINET IO	
• Number of RJ45 ports	2
Cable length	
— Cu conductors	100 m
Standards, approvals, certificates	
Railway application	
• EN 50121-3-2	Yes; EMC for rail vehicles
• EN 50121-4	Yes; EMC for signal and telecommunications systems
• EN 50124-1	Yes; Railway applications - overvoltage category OV2; pollution degree PD2; rated surge voltage UNi = 0.5 kV; UNm = 24 V DC
• EN 50125-1	Yes; Rail vehicles - see ambient conditions
• EN 50125-2	Yes; Stationary electrical equipment - see ambient conditions

- EN 50125-3 Yes; Signal and telecommunications systems - see ambient conditions; vibrations and shocks: Application point outside of tracks (1 m to 3 m away from track)
- EN 50155 Yes; Rail vehicles - temperature class Tx, horizontal mounting position, salt spray Class ST2
- EN 61373 Yes; Rail vehicles - vibrations and shocks: Category 1 Class A/B
- Fire protection acc. to EN 45545-2 Yes; Rail vehicles - verification on request

Ambient conditions

Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on land craft, rail vehicles and special-purpose vehicles	
— to biologically active substances according to EN 60721-3-5	Yes; Class 5B2 mold, fungus and dry rot spores (with the exception of fauna); Class 5B3 on request
— to chemically active substances according to EN 60721-3-5	Yes; Class 5C3 (RH < 75 %) incl. salt spray acc. to EN 50155 (ST2); *
— to mechanically active substances according to EN 60721-3-5	Yes; Class 5S3 incl. sand, dust; *
from supply voltage 1L+	
— Note regarding classification of environmental conditions acc. to EN 60721	* The supplied plug covers must remain in place over the unused interfaces during operation!

Dimensions

Width	20 mm
Height	69.5 mm
Depth	59 mm

Weights

Weight, approx.	46 g
-----------------	------

Other

Note:

For use in railway applications, also observe the product information "SIPLUS extreme RAIL" A5E37661960A Online Support article 109736776

last modified:

05/16/2018