Product data sheet Characteristics

CSU36162502

Stago - cross piece flat - 60x250 mm - steel - pregalvanized



ľ	VI	а	ı	r

Range of product	Stago
Product or component type	X-junction
Environmental characteristic	For partly outdoor environment with low exposure to corrosion, such as ware-houses and parking garages

Complementary

ange of product Stago		
Product or component type	X-junction	
Environmental characteristic	For partly outdoor environment with low exposure to corrosion, such as ware-houses and pa garages	
Complementary		
Operating angle	90 °	
Direction change type	Horizontal	
Adjustment	Foldable	
Product destination	KG281 cable tray 60 mm height and 250 mm width KB184 cable tray 60 mm height and 250 mm width KB284 cable tray 60 mm height and 250 mm width	
Mounting mode	Push-in	
Fixing mode	By joint screwless Screwless	
Material	Steel, pre-galvanized	
Atmospheric-corrosivity category	C2	
Height	60 mm	
Width	250 mm	
Product weight	1.496 kg / set of 100	
Offer Sustainability		
RoHS (date code: YYWW)	Compliant - since 1101 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product end of life instructions	Need no specific recycling operations	
C	SU36162502	

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1101 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	-
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product end of life instructions	Need no specific recycling operations	<u>2.</u> 2. 2.