

Product data sheet

Characteristics

CSU4518360

Performa - mesh tray - ZnAl (Zinc-Aluminium) - 105 mm x 600 mm x 3000 mm



Main

| | |
|---------------------------|-----------|
| Range of product | Performa |
| Product or component type | Mesh tray |
| Quantity per set | 6 m |

Complementary

| | |
|----------------------------------|---|
| Shape | U-shape |
| Material | Steel, zinc+ |
| Atmospheric-corrosivity category | C3/C4 |
| Longitudinal wire diameter | 4.9 mm |
| Transversal wire diameter | 3.9 mm |
| Cable cross section | 59568 mm ² |
| Standards | EN 50102 IEC 61537 IEC 60068-2-75 DIN 4102-12 EN/ISO 9227 EN 10244-2 |
| Length | 3 m |
| Height | 110 mm |
| Width | 600 mm |
| Height compatibility | 105 mm |
| Width compatibility | 600 mm |
| Surface treatment compatibility | Zinc+ |

Environment

| | |
|---------------------------------------|--------------|
| Ambient air temperature for operation | -40...120 °C |
| IK degree of protection | IK10 |

Offer Sustainability

| | |
|------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 1201 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |

Reference not containing SVHC above the threshold

Product end of life instructions

Need no specific recycling operations
