



Main

Range of product	Performa
Product name	Palt
Product or component type	Mesh tray
Quantity per set	24 m

Complementary

Shape	U-shape
Material	Steel C4D, hot-dip galvanized
Atmospheric-corrosivity category	C3/C4
Longitudinal wire diameter	3.9 mm
Transversal wire diameter	3.9 mm
Standards	IEC 61537 IEC 60068-2-75 DIN 4102-12 EN/ISO 1461 EN/ISO 9227 EN 50102
Length	3 m
Height	60 mm
Width	60 mm
Height compatibility	60 mm
Width compatibility	60 mm
Surface treatment compatibility	Hot-dip galvanized

Environment

Ambient air temperature for operation	-40...120 °C
IK degree of protection	IK10

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------