



Main

|                              |  |
|------------------------------|--|
| Range of product             | Stago  |
| Product or component type    | Cable tray   |
| Cable support type           | Perforated   |
| Environmental characteristic | For area with almost permanent high levels of humidity and airborne pollution, such as tunnels and dockyards |

Complementary

|                                  |  |
|----------------------------------|--|
| Product destination              | ES114 cable tray                       |
| Fixing mode                      | By screw                               |
| Material                         | Stainless steel AISI 304               |
| Atmospheric-corrosivity category | C5-I                                   |
| Thickness                        | 1 mm                                   |
| Perforation location             | Side perforation<br>Bottom perforation |
| Nominal cross section            | 55000 mm <sup>2</sup>                  |
| Height                           | 110 mm                                 |
| Width                            | 500 mm                                 |
| Length                           | 3000 mm                                |
| Product weight                   | 5.334 kg / 100 m                       |

Offer Sustainability

|                               |   |
|-------------------------------|---|
| Sustainable offer status      | Green Premium product   |
| RoHS (date code: YYWW)        | Compliant - since 1101 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                         | Reference not containing SVHC above the threshold<br>Reference not containing SVHC above the threshold                                |
| Product environmental profile | Available   |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

