



Main

| | |
|------------------------------|--|
| Range of product | Stago |
| Product or component type | Stop end/reducer |
| Device short name | H45 |
| Cable support type | High side |
| Environmental characteristic | For partly outdoor environment with low exposure to corrosion, such as ware-houses and parking garages |

Complementary

| | |
|----------------------------------|--|
| Product destination | Cable ladder LB4000 100 mm height and 300 mm width |
| Mounting mode | Push-in |
| Fixing mode | By nut |
| Material | Steel, pre-galvanized |
| Atmospheric-corrosivity category | C2 |
| Perforation location | Side perforation |
| Height | 143 mm |
| Width | 439 mm |
| Depth | 1 mm |
| Product weight | 0.39 kg / set of 1 |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1101 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications