

Product data sheet

Characteristics

CSU76701534

Stago - ES114 tray perforated 60x150mm L=3m
1mm stainless steel AISI 304



Main

| | |
|------------------------------|--|
| Range of product | Stago |
| Product or component type | Cable tray |
| Cable support type | Perforated |
| Environmental characteristic | For area with almost permanent high levels of humidity and airborne pollution, such as tunnels and dockyards |

Complementary

| | |
|----------------------------------|--|
| Product destination | ES114 cable tray |
| Fixing mode | By screw |
| Material | Stainless steel AISI 304 |
| Atmospheric-corrosivity category | C5-I |
| Thickness | 1 mm |
| Perforation location | Side perforation Bottom perforation |
| Nominal cross section | 9000 mm ² |
| Height | 60 mm |
| Width | 150 mm |
| Length | 3000 mm |
| Product weight | 1.98 kg / 100 m |

Offer Sustainability

| | |
|----------------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 1101 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product end of life instructions | Need no specific recycling operations |

CSU76701534