



Main

| | |
|---------------------------|------------------------|
| Range | Wibe |
| Range of product | Wibe Cable Ladders |
| Product name | Wibe Cable Ladders |
| Product or component type | Cable ladder |
| Device short name | KHZSP |
| Device application | Industrial application |

Complementary

| | |
|----------------------------------|---------------------------|
| Type of side profile | Open profile |
| Type of rung | Perforated profile |
| Mounting location | Indoor Outdoor |
| Rung dual spacing | 250 mm |
| Material | Stainless steel AISI 316L |
| Atmospheric-corrosivity category | C5-M |
| Height | 55 mm |
| Width | 198 mm |
| Length | 3 m |
| Product weight | 198 kg / 100 m |

Environment

| | |
|------------------------------|---|
| Environmental characteristic | For area with almost permanent high levels of humidity, airborne pollution and salt, such as purify-ing plants and offshore |
| Standards | IEC 61537 |

Offer Sustainability

| | |
|--------------------------|-----------------------|
| Sustainable offer status | Green Premium product |
|--------------------------|-----------------------|

CSU794439

| | |
|----------------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 1152 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |