



Main

Range	TeSys
Product name	TeSys B
Product or component type	Contactor
Device short name	CV1BH
Contactor application	Motor Resistive circuits, heating, lighting
Utilisation category	AC-3 AC-1
Control circuit type	DC
Pole contact composition	2 NC
[Ie] rated operational current	300 A AC for power circuit
Current rating code of contactor	BH
Auxiliary contact composition	2 NO + 2 NC
[Uc] control circuit voltage	220 V DC

Complementary

Auxiliary contacts type	Type instantaneous (2 NO + 2 NC)
Control circuit voltage limits	0.85...1.1 U _c at (<= 55 °C) operational 0.1...0.65 U _c at (<= 55 °C) drop-out
[Ui] rated insulation voltage	690 V - conforming to IEC 60947-4
[Ue] rated operational voltage	690 V AC
[I _{th}] conventional free air thermal current	200 A at <= 40 °C
Mechanical durability	5000000 cycles
Operating rate	<= 120 cyc/mn at <= 55 °C
Compatibility code	CV1BH

Environment

Standards	EN 60947-4 IEC 60947-4
Product certifications	Bureau Veritas CEI
IP degree of protection	IP00 conforming to IEC 60529

Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	2000 m
Shock resistance	4 gn for frequencies <= 30 Hz 2 gn for frequencies > 30 Hz
Vibration resistance	4 gn for frequencies <= 30 Hz 2 gn for frequencies > 30 Hz

Offer Sustainability

RoHS (date code: YYWW)	Will not be compliant Will not be compliant
------------------------	--