



### Main

Range of product	Digilink
Range	Digilink
Product or component type	Patch cord
Cable shielding type	UTP
Colour tint	Yellow

### Complementary

Type of cable	4 twisted-pairs cable
Communication network category	6
Connector type	RJ45
Material	PC (polycarbonate) plug
AWG gauge	AWG 23 stranded cable
Insulation resistance	$\geq 500$ mOhm @ 500 V DC
Contacts material	Gold over nickel
[In] rated current	$\leq 1.5$ A
Contact resistance	$\leq 20$ mOhm
[Ue] rated operational voltage	$< 72$ V DC
Cable length	3 m

### Environment

Flame retardance	UL 94 V-0
Standards	ANSI/TIA-568-C.2 ISO/IEC 11801 class E
Product certifications	UL listed UL/ETL verified

### Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1101 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

---

Product end of life instructions	Need no specific recycling operations
----------------------------------	---------------------------------------

---

**Contractual warranty**

---

Warranty period	18 months
-----------------	-----------

---