



### Main

Range of product	Digilink
Range	Digilink
Product or component type	Patch panel
Provided equipment	With RJ45 connectors
Communication network category	6
Accessory / separate part designation	Insulation displacement connector
Cable shielding type	UTP
Number of port	24

### Complementary

Connector type	RJ45
Number of matings	750 cycles
[In] rated current	$\leq 1.5$ A
Insulation resistance	$\geq 500$ mOhm @ 500 V DC
Contact resistance	$\leq 20$ mOhm
Material	Powder coated steel panel
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Width	482.6 mm
Height	44.2 mm
Number of rack unit	1U

### Environment

Environmental characteristic	Flame retardant
Product certifications	UL listed UL/ETL verified
Standards	EIA/TIA TSB 40 A ANSI/TIA-568-C.2 ISO/IEC 11801 class E

### Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1101 - Schneider Electric declaration of conformity
------------------------	---

 Schneider Electric declaration of conformity

---

REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
-------	--

---

Product end of life instructions	Need no specific recycling operations
----------------------------------	---------------------------------------

---

Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---