



### Main

Range of product	Digilink
Product or component type	Modular jack
Cable shielding type	UTP
Communication network category	5e
Colour tint	Yellow

### Complementary

Connector type	RJ45
Type of footprint	Keystone
Insulation resistance	$\geq 500$ mOhm @ 500 V DC
Number of matings	750 cycles
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Pulling force	140 N
Delay skew	$\leq 2.5$ ns @ 1...100 MHz
[In] rated current	$\leq 1.5$ A
Contact resistance	$\leq 20$ mOhm
[Ue] rated operational voltage	$< 72$ V DC

### Environment

Flame retardance	UL 94 V-0
Product certifications	UL listed UL/ETL verified
Standards	ISO/IEC 11801 class D ANSI/TIA-568-C.2

### Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1745 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product end of life instructions	Need no specific recycling operations

Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---