



Main

| | |
|---------------------------|------------|
| Range of product | Digilink |
| Range | Digilink |
| Product or component type | Patch cord |
| Cable shielding type | UTP |
| Colour tint | Grey |

Complementary

| | |
|--------------------------------|----------------------------|
| Type of cable | 4 twisted-pairs cable |
| Conductor material | Copper |
| Number of conductors | 1 |
| Communication network category | 5e |
| Connector type | RJ45 |
| Material | PC (polycarbonate) plug |
| AWG gauge | AWG 24 stranded cable |
| Insulation resistance | ≥ 500 mOhm @ 500 V DC |
| Contacts material | Gold over nickel |
| [In] rated current | ≤ 1.5 A |
| Contact resistance | ≤ 20 mOhm |
| [Ue] rated operational voltage | < 72 V DC |
| Cable length | 2 m |

Environment

| | |
|------------------------|---|
| Flame retardance | UL 94 V-0 |
| Standards | ANSI/TIA-568-C.2 ISO/IEC 11801 class D |
| Product certifications | UL listed UL/ETL verified |

Offer Sustainability

| | |
|------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 1101 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
|------------------------|---|

| | |
|----------------------------------|---------------------------------------|
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
