



### Main

|                           |            |
|---------------------------|------------|
| Range of product          | Digilink   |
| Range                     | Digilink   |
| Product or component type | Patch cord |
| Cable shielding type      | UTP        |
| Colour tint               | Blue       |

### Complementary

|                                |                            |
|--------------------------------|----------------------------|
| Type of cable                  | 4 twisted-pairs cable      |
| Communication network category | 5e                         |
| Connector type                 | RJ45                       |
| Material                       | PC (polycarbonate) plug    |
| AWG gauge                      | AWG 24 stranded cable      |
| Insulation resistance          | $\geq 500$ mOhm @ 500 V DC |
| Contacts material              | Gold over nickel           |
| [In] rated current             | $\leq 1.5$ A               |
| Contact resistance             | $\leq 20$ mOhm             |
| [Ue] rated operational voltage | $< 72$ V DC                |
| Cable length                   | 5 m                        |

### Environment

|                        |   |
|------------------------|---|
| Flame retardance       | UL 94 V-0                                 |
| Standards              | ANSI/TIA-568-C.2<br>ISO/IEC 11801 class D |
| Product certifications | UL listed<br>UL/ETL verified              |

### Offer Sustainability

|                                  |   |
|----------------------------------|---|
| RoHS (date code: YYWW)           | Compliant - since 1101 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations   |

Contractual warranty

---

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

---