



Main

Range of product	Digilink
Range	Digilink
Product or component type	Patch panel
Provided equipment	With RJ45 connectors
Communication network category	5e
Cable shielding type	UTP
Number of port	24

Complementary

Connector type	RJ45
Number of matings	750 cycles
[In] rated current	≤ 1.5 A
Insulation resistance	≥ 500 mOhm @ 500 V DC
Contact resistance	≤ 20 mOhm
Material	Powder coated steel panel
Contacts material	Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel
Width	482.6 mm
Height	44.2 mm
Number of rack unit	1U

Environment

Environmental characteristic	Flame retardant
Product certifications	UL/ETL verified
Standards	ANSI/TIA-568-C.2 ISO/IEC 11801 class D EIA/TIA TSB 40 A

DCEPP24UKY1U

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1101 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------