



Overview

| | |
|----------------------|--|
| Model Name | Magnum VS 100 W/SNMP -- 4X30A CB Distribution |
| Includes | Rack Mounting brackets , User Manual |
| Standard Lead Time | Usually Ships within 4 Weeks |
| Product Distribution | Albania , Algeria , Andorra , Angola , Armenia , Austria , Azerbaijan , Bahrain , Belarus , Belgium , Benin , Bosnia And Herzegovina , Botswana , Bulgaria , Burkina Faso , Burundi , Cambodia , Cameroon , Canada , Central African Republic , Chad , Congo , CONGO, THE DEMOCRATIC REPUBLIC OF THE , Cote D'Ivoire , Croatia , Cyprus , Czech Republic , Denmark , Djibouti , Egypt , Equatorial Guinea , Eritrea , Estonia , Ethiopia , Finland , France , Gabon , Gambia , Georgia , Germany , Ghana , Gibraltar , Greece , Guadeloupe , Guinea , French Guiana , Hungary , Iceland , Iran (Islamic Republic Of) , Iraq , Ireland , Israel , Italy , Jordan , Kazakhstan , Kenya , Kuwait , Latvia , Lebanon , Lesotho , Liberia , Liechtenstein , Lithuania , Luxembourg , Macedonia , Madagascar , Malawi , Mali , Malta , Martinique , Mauritania , Mauritius , Mayotte , Moldova, Republic Of , Mongolia , Morocco , Mozambique , Namibia , Netherlands , Niger , Nigeria , Norway , Oman , Pakistan , Poland , Portugal , Reunion , Romania , Russian Federation , Rwanda , Saudi Arabia , Senegal , Sierra Leone , Slovakia (Slovak Republic) , Slovenia , Somalia , South Africa , Spain , Sudan , Suriname , Sweden , Switzerland , Tajikistan , TANZANIA, UNITED REPUBLIC OF , Togo , Tunisia , Turkey , Turkmenistan , Uganda , Ukraine , United Arab Emirates , United States , Uzbekistan , Western Sahara , Yemen , Zambia , Zimbabwe |

Communications & Management

| | |
|---------------|---|
| Control panel | LED status display of rectifier healthy , Network link status LED |
| Control panel | Current Limit , Distribution Failure , Input OK , Major Alarm , Minor Alarm , Output OK , Over Voltage , User Defined |
| Control panel | Major Alarm , Minor Alarm , User Defined |

Output

| | |
|--------------------------------|-------------------------|
| Output Power Capacity | 500.0 Watts / 10.0 VA |
| Max Configurable Power (Watts) | 5000.0 Watts / 105.0 VA |
| Nominal Output Voltage | 48 |
| Nominal Output Voltage | Positive ground |
| Nominal Output Voltage | Positive ground |
| Nominal Output Voltage | Battery circuit |
| Nominal Output Voltage | Battery circuit , None |
| Nominal Output Voltage | 0.0 mV |
| Nominal Output Voltage | 0.0 dBmC |

| | |
|------------------------------|------------|
| Nominal Output Voltage | 0.0 mV p-p |
| Nominal Output Voltage | 0.0 mV RMS |
| Protection Device 1 Quantity | 0 |
| Protection Device 2 Quantity | 0 |
| Protection Device 3 Quantity | 0 |
| Protection Device 3 Quantity | 54.0 |

Input

| | |
|---|---------------------------------|
| Nominal Input Voltage | 100~~120~~200~~208~~230V |
| Input Frequency | 47 - 63 Hz |
| Input Connections | Hard Wire 3-wire |
| Input voltage range for main operations | 88 - 264 V |
| Input Power Factor at Full Load | 0.99 |
| Maximum Input Current per phase | 5.5 |
| Input Overcurrent Protection | Integral fuse in each rectifier |

Batteries & Runtime

| | |
|--------------|--|
| Battery Type | No internal battery - uses external battery system |
|--------------|--|

Physical

| | |
|------------------|----------|
| Maximum Height | 267.0 mm |
| Maximum Width | 438.0 mm |
| Maximum Depth | 330.0 mm |
| Rack Height | 6 U |
| Net Weight | 18.0 kg |
| Shipping Weight | 23.0 kg |
| Shipping Height | 387.0 mm |
| Shipping Width | 559.0 mm |
| Shipping Depth | 470.0 mm |
| Color | Black |
| Units per Pallet | 0.0 |

Conformance

| | |
|-------------------|--|
| Approvals | CE , EN 55022 Class A , EN 55024 , EN 61000-3-2 , EN 61000-3-3 , FCC Part 15 Class A , UL 1950 |
| Standard warranty | 2 years repair or replace |

Sustainable Offer Status

| | |
|--------------------------------|------------|
| RoHS | Compliant |
| Other Environmental Compliance | China RoHS |